

REINHOLD ENVIRONMENTAL Ltd.



2010 APC Round Table & Expo Presentation

July 18-20, 2010, in Concord, NC / Hosted by Duke Energy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.



SO₃ MITIGATION SYSTEMS RECENT EXPERIENCE

Mark Thomas

Duke Energy



Presentation Overview



- Interactive Discussion
 - Shared Experiences
 - General Info, Specific where possible
- Basics/ Mitigation Fundamentals
- BOP Issues
- Recent Experience
- Future Advancements



SO₃ IMPACTS



NEGATIVE

- Plume Opacity
- Air Heater Pluggage
- Duct & Fan Corrosion
- Reduced Hg/HAP Capture
- Catalyst ABS
- SCR AIG Pluggage
- Baghouse Pluggage

POSITIVE

- ESP Conditioning



VISIBLE PLUME



- Opacity due to small quantities of H_2SO_4 (Sulfuric Acid) Aerosols in Flue Gas
- Aerosols produced from SO_3 in flue gas when quenched in Absorber Mods




How SO₃ is Formed




In Boiler approx 1% of SO₂ oxidizes to form SO₃

In SCR additional 0.75% -to-1.5% of SO₂ oxidizes to form SO₃. Vanadium in SCR serves as catalyst for this reaction.



Physical Forms of SO₃





SO₃ MITIGATION FUNDAMENTALS



Gas Phase Capture

- Molecular Gas Kinetics Drives Reaction with Sorbents
- Distribution of Sorbent Most Critical Requirement

Liquid Phase (Aerosol) Capture

- Aerosol Droplet Momentum & Static Charge Used to Capture
Ex: WFGD, WESP
- Condensation onto Particulate Matter

Inhibit Formation

- Reduce SCR Temps
- SCR Catalyst Formulation – Low Oxidation Catalyst
- Reduce SO₂ ie Fuel Change



SO₃ MITIGATION SORBENT OPTIONS



CALCIUM SORBENTS

- Hydrated Lime - Dry Ca(OH)_2
- Quick Lime - Dry CaO
- Limestone -Dry CaCO_3

SODIUM SORBENTS


- SBS Soda Ash - Wet Na_2CO_3
- Trona - Dry $\text{Na}_2\text{CO}_3 + \text{NaHCO}_3 + 2\text{H}_2\text{O}$
- Sodium BiCarbonate NaHCO_3

MAGNESIUM SORBENTS

- Magnesium Hyrdoxide – Wet Mg(OH)_2
- Magnesium Oxide – Dry MgO
- Magnesite (Mag Carbonate) – Dry MgCO_3



SO₃ MITIGATION STRATEGIES





System Issues



Dry System Issues

- Poor Distribution
- Feed Interruptions
- Lance Pluggage
- Piping Scaling
- Duct Deposits
- Reagent Quality
- Reagent Storage & Handling

Wet System Issues

- Duct Deposits
- Lance Deposits
- Lance Corrosion
- Nozzle Pluggage (Slurries)



SO₃ Mitigation System Improvements



Wet System Improvements

- Lance Redesign
- Pump Upgrades
- Vendor R&D Ongoing

Dry System Improvements

- Better Reagent Distrib & Mixing
 - More Lances
 - Dispersion Plates
- Trona Milling On Site
- Better Fluidization in Silo
- Reduced Lance Pluggage
- Sight Glasses
- Powder Flow Meters
- Simplification



SO₃ Mitigation - Recent Experience



- Duke Experience – Last 12 Months
 - Hydrated Lime
 - Pre-SCR Hydrated Lime Injection Trial
 - Trona
 - Pre-SCR Milled Trona Injection Trial
 - Milled Trona Trials (for SO₂)
 - SBS
 - Pre-SCR SBS Injection – Extended Trial
 - Magnesium Hydroxide – Furnace Injection
 - Magnesite – Coal Additive
- Southern Company Recent Experience
 - New Trona System
- Others



Duke Energy - Recent SO₃ Mitigation Experience




Pre-SCR Trona Injection Trial – Fall 2009

- 1300 Mw Unit
 - SCR – ESP – WFGD (Thiosorbic Lime)
- Milled Trona Injected at Econ Outlet
- Measured SO₃ & HCl @ APH Inlet
- Objective
 - Prove incrs SO₃ removal w/ incrs residence time
 - Prove increased efficiency with milled Trona
 - D50 ~30-40um >>>D50 12-15um



Duke Energy - Recent SO₃ Mitigation Experience





Duke Energy - Recent SO₃ Mitigation Experience



Pre-SCR Trona Injection Trial – Findings

- Low levels of SO₃ can be achieved <5ppm @APH Inlet
 - Required higher injection rates than expected
 - Loss to SO₂ Possible Reason
 - Able to eliminate condensables
- 15-40% HCl removal @ APH Inlet
- Mill cleaning daily required
- Effect on Catalyst Uncertain (Likely not good)
- Effect on Catalyst Hg Oxidation uncertain



Duke Energy - Recent SO₃ Mitigation Experience



Pre-SCR Hydrated Lime Injection Trial – Findings

- Low levels of SO₃ can be achieved <5ppm @APH Inlet
 - Required higher injection rates than expected
 - Loss to CO₂ Possible Reason
 - Able to eliminate condensables
- 40-65% HCl removal @ APH Inlet
- Effect on SCR Catalyst Uncertain
- Effect on Catalyst Hg Oxidation Uncertain



Duke Energy - Recent SO₃ Mitigation Experience



Pre-SCR SBS Injection

- Injected SBS/Soda Ash continuously ahead of B-Side SCR
- Objectives
 - Eliminate APH Pluggage
 - Eliminate ESP Perf Plate and Duct Deposits



Duke Energy - Recent SO₃ Mitigation Experience



Pre-SCR SBS Injection - Findings

- Able to achieve Ultra Low SO₃ levels
- Able to eliminate Condensables
- Required Higher than expected feedrates
 - SO₂?
 - Sodium maldistribution?
- ESP increased Opacity due to low SO₃
- Apparent increased SCR Catalyst Deactivation



Lessons from Mitigation Trials



- Make sure you know your **objectives**
 - Determine critical information prior test campaign
 - Design Test campaign to focus on critical info primarily
 - Multi Million Dollar Decisions can be made using incomplete data
- Test Data from different Units often not interchangeable
 - Scrutinize assumptions carefully
 - Be careful not to credit potential benefits which could be achieved in another manner.
 - Ex: APH Pluggage reduction
 - Be careful not to assume issues/ effects in past will be same now
- Include all significant Impacts in Cost/Benefit Analysis



SO₃ Mitigation Process Advancement



- Progress from SO₃ Focus to Co-Benefits /Multi Pollutant Focus
- Integrated Environmental Control / BOP Analysis
 - Corrosion
 - APH Pluggage
 - SCR Turndown
 - Baghouse Protection
 - HAPs/ HCl/Hf effects on FGD
 - Arsenic Mitigation/ Catalyst Protection
 - Potential SCR Catalyst Degradation
 - Furnace Slagging
 - Plume Opacity



SO₃ Mitigation Path Forward



- Unresolved Issues Require Testing
 - Prove SO₃ reduction required to avoid APH pluggage
 - Catalyst Poisoning from Pre SCR Reagent Injection
 - Requires cost/ benefit analysis
 - HCl/ Hf/ HAPs removal vs SO₃ removal
 - Hg Ox impacts from Pre SCR HCl removal
 - Long Term Milling effectiveness and reliability
 - Continue to reduce Lime scaling



SO₃ Mitigation – Recent Experience



- Southern Co. - TronSystem
- Others



SO₃ Mitigation – Recent Experience



QUESTIONS??