

REINHOLD ENVIRONMENTAL Ltd.



2010 APC Round Table & Expo Presentation

July 18-20, 2010, in Concord, NC / Hosted by Duke Energy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.




How condition monitoring can reduce fabric filter operating costs (and some challenges)

Rod Hansen

Eskom Power Stations

- Total generating capacity of 42 830 MW, spread across 20 power stations
- 37 558 MW coal fired (T)
- 600 MW hydroelectric (H)
- 1 930 MW nuclear (N)
- 1 400 MW pumped storage (P)
- 1 342 MW gas turbine (oil fired) (G)



Introduction

Eskom is South Africa's State owned electric utility.

Established in 1923, now one of the world largest coal burning utility (+ 120 Mt annually).

Eskom has a total generating capacity of 42 830 MW with the following energy mix:

Coal 33 758 MW

Return to Service (Coal) 3 800 MW

Hydroelectric 600 MW


Nuclear 1 930 MW

Pumped Storage 1 400 MW

Gas Turbines 1 342 MW

11000 MW in pipeline, first by 2013, fast tracked (coal, pumped storage, gas turbine, wind, solar....)

Particulate Emissions (Historical)






Bag Filters Condition Monitoring


- Routine Fabric Filter Condition Monitoring
- Trial Bags Programme
- The Duvha epic
- Majuba Unit 3 Bags Failure Investigations
- Arnot Unit 5 Fabric Investigation
- Hendrina PPS Fabric Materials Comparison

CROSS-SECTION OF FIBRES


POLYPHENYLENE SULPHIDE



ACRYLIC



POLYIMIDE



Fabric Filter Primary Laboratory Testing

- Residual tenacity measurement (*Lloyds* tensile tester)
 - tearing and tensile strength
 - elongation at break
- Air permeability (*Wira* Air Permeator)
- Residual dust mass
- pH (*Crison* pH meter with temperature compensation)
- Mullen's bursting strength
- Scanning Electron Microscopy (SEM)
- Energy Dispersive Spectroscopy (EDS)
 - quantitative and qualitative elemental analysis under SEM



Fabric Filter Specialised Laboratory Testing

- Photo-acoustic Fourier Transform Infrared Spectroscopy (PAS FTIR)
 - fibre identification
 - degradation kinetics
- Thermo-gravimetric analysis (TGA)
 - loss of mass against temperature
 - sample identification, degradation onset
- Differential scanning calorimetry (DSC)
 - thermal properties of fibres, melting point, cristalinity
- Dynamic Contact Analyser (DCA)
 - surface tension analysis
 - degree of chemical degradation

Recipe?

- Weight
- Needleing
- Filtration batt / membranes?
- Singing
- Calandering
- Heat treatment
- Fibre denier
- Fibre blends – PPS/P84/PTFE
- Scrim
- QA/QC

Eskom's PJFF Plants

STATION	UNIT	No. OF BAGS/UNIT	BAG LIFE	BAG TYPE
Arnot	1 to 3	13 584	35 000	PPS/PTFE/PI
	4 to 6	10 934	32 000	PPS/PI
Camden	1 to 4, 7 & 8	9 616	35 000*	PPS/PI
Duvha	1 to 3	26 928	35 000	PPS/PI
Grootvlei	1, 5 & 6	8 832	40 000*	PPS/PI
Hendrina	1, 6 to 10	8 074, 7 984	36 000	PPS
	2 to 5	8 160	32 000	PAN
Majuba	1 to 3	30 976	25 000	PAN/PI
	4 to 6	32 512	25 000	PAN/PI

Duvha Power Station




Fabric Filters – Brief Background - cont

- **Enhancement Options Investigated During 1990**
- **Installation of complete new ESP's and a SO₃ plant.**
- **Upgraded ESP's with the latest technology and a SO₃ plant.**
- **Pulse Jet Fabric Filters**
 - **Pre-qualification required the installation of pilot plants.**
 - **3 Suppliers installed pilot plants.**
 - **Pilot plant test results were evaluation during 1992.**
 - **Project was awarded to and construction started in 1993.**
 - ✓ **Unit 1 commissioned in July 1993.**
 - ✓ **Unit 2 commissioned in Dec 1993.**
 - ✓ **Unit 3 commissioned in June 1994.**



Fabric Filters Pilot Plants





Duvha -ash deposits on tube plate

Duvha Performance

- Premature fabric failure
- Acid enrichment of fibres: degradation
- Improved performance; achieved 18500 hrs
 - fuel oil
 - higher DP control set point
 - better operation
- Bag failure pattern
- SO₃ Neutralisation Plant
 - selection of viable systems
 - demonstration plant
 - Converting of the plants to high temperature filtration materials: PPS/PI composite
- Expected bag life after modifications: 28000 hrs

DUVHA


a big challenge !!!

Marrying fabric properties to ash chemistry

- premature failures caused by acid enrichment resulting in acid degradation of fabrics
- Duvha ash chemistry does not neutralise naturally formed SO_3

IDEAL ASH CHARACTERISTICS

- Outer CaO layer
- Inner quartz layer




CaO is available to neutralise any acid absorbed onto the ash particles.

DUVHA ASH CHARACTERISTICS



- CaO forms gelhenite during combustion
- Ca is therefore inert and cannot neutralise the acid




No Neutralisation can occur, hence acid enrichment occurs on the surface of the particles

**Gelhenite $[\text{CaAl}_2\text{SiO}_7]$ is formed at 1100°C +
during combustion**

Reaction between Kaolinite $\text{Ca}(\text{C-H-O})$ and CaCO_3


HOW CAN THE ACID ENRICHMENT BE STOPPED ?

- by neutralising the SO_3 in the flue gas
- pilot plant tests have shown that the injection of hydrated lime ($\text{Ca}(\text{OH})_2$) neutralises the SO_3



Results – Reduction in Particulate Emissions

Duvha Relative Emission Performance
1984 to 2004



Duvha Conclusion

- Bag filter costs reduced from R2.09/Mwh to R1.53/Mwh.
- The total bag filter operational costs = R1.53/Mwh.
- The total ESP and SO₃ Plant operational costs = R0.99/Mwh.

Arnot Power Station



Arnot Performance


- High temperature bags: Procon (PPS)
- Temperature excursion, unit 4 LH
- Control philosophy
- Tube plate sealing leaks: modification for units 1, 2 & 3
- Pulse pipe design modification
- Life prediction: 30 000 – 43 000 hours
- Failure mode: breaking of material / abrasion
- Future plans: improved specification
- Composite material used for the new sets of bags



Tube plate leaks




Arnot U5 PPS/P84 25000hrs





Arnot U5 PPS/P84 25000hrs





Failure Mode and New Specification

- Failure mode identification
 - Localised erosion areas (exception)
 - Fabric damaged due to inadequate length
- Bag house chemistry
 - CaO in dust is reactive
- Future bag characteristics
 - Fine fibre surface area required with the existing pulsing system
 - Fabric residual strength has to be increased
- New specification based on:
 - hybrid scrim: 33% PTFE + 67% PPS
 - hybrid batt: PPS + PPS and P84 mixture on the surface



MAJUBA

-some technical insight-

Majuba Power Station FFP



Majuba Design

- Bag material: PAN and PAN/PI composite
- Fibres: Dralon T, Dolanit & Ricem
- Pulsing system: Low pressure / high volume
- Number of bags: about 31000 - 33000
- Number of cells: 8




Majuba Performance

- Flow distribution
- Tube plate buckling
- Hopper heater elements failure
- Shrinking of bags, lifting of manifolds
 - Dolanit vs Ricem
- Good performance to date
- Two shifting operating mode
- Predicted bag life: 20000 - 22000 hours
- Achieved life: 23000

MAJUBA

U1 - 6

cause	symptom	cure
Load cycling 2 shifting = excessive dew point exposure	<ul style="list-style-type: none"> ▪ Shortened bag life 	<ul style="list-style-type: none"> ▪ Precoating ▪ Thicker dust cake ▪ Keep warm
Flow design, bottom entry, low pressure random pulsing	 pulse wave distribution	<ul style="list-style-type: none"> ▪ CFD ▪ Reduce jetting

Majuba Trial Bags Shrinkage Investigation





Shrinkage Measurement on a Trial Bag



Shrinkage Measurement at 6 874 Hours



Longer than normal bags (unit 5)



Hendrina Power Station



Hendrina Performance

- Fabric shrinkage
- Initial life: 26000 hours
- Present life: 34000 hours (PAN) and 38000 hours (PPS)
- Temperature and chemical degradation
- Revised bag specification
- Good quality checks
- Control philosophy
- In-situ bag filter cleaning





New ESP Conversions to FFP in Eskom

AND LASTLY

➤ CAMDEN

- 8 Boilers retrofitted with FFPs
- 4 compartments per boiler
- Bag material: PPS/PI composite and PPS/PI composite with PPS/PTFE Hybrid scrim

■ GROOTVLEI

- 3 Boilers retrofitted with FFPs
- Bag material: PPS/PI composite with PPS/PTFE Hybrid scrim



THANKS – QUESTIONS?

For Further Info, please contact...

RE Consulting

**3850 Bordeaux Drive
Northbrook, IL. 60062**

Phone: 847-562-8556

Fax: 847-562-8894

Email: greinhold@reconsulting.info