

REINHOLD ENVIRONMENTAL Ltd.



2010 APC Round Table & Expo Presentation

July 18-20, 2010, in Concord, NC / Hosted by Duke Energy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

SOUTHERN RESEARCH

Legendary Discoveries. Leading Innovation.

APC with COHPAC[®] and TOXECON[®] Fabric Filters

**2010 Reinhold APC Roundtable and EXPO
July 19-20, 2010**

Overview

- Introduction
- ESP and FF Performance Improvements
- COHPAC[®] Technology
- TOXECON[®] Technology
- Summary


ESP and FF Performance Improvements

- Over the last 30 years there have been a number of developments to improve the particulate collection performance of ESPs and FFs, as well as reduce their O&M costs.
- Precipitators have seen the advent of pulsed power supplies, a variety of RDE styles, digital AVCs with sophisticated GUI displays and data logging capabilities.
- Low ratio baghouses have seen the common use of sonic horns for improved bag cleaning (low ratio) and the development of a number of new pulse-jet filter fabrics for improved collection and lower pressure drop.


ESP and FF Performance Improvements

- Also, during this time a number of unique APC concepts have been developed or licensed by various organizations to attain a special market niche.
- Electrostatically Stimulated Fabric Filtration (ESFF) was developed by EPA, tested by Southern Research, and licensed by GE (BHA Group) as their MAX-9[®] design.
- Several pilot-scale tests of the ESFF technology have taken place.
- Pilot-scale testing demonstrated improvement in fine particle collection and a significant decrease in the rate of pressure drop increase during filtration cycles as shown in the next two slides.
- MAX-9[®] has not yet been installed at full-scale.

Electrostatically Stimulated Fabric Filtration




Electrostatically Stimulated Fabric Filtration



Advanced Hybrid Particulate Collector

- The Advanced Hybrid technology was developed by the Energy and Environmental Research Center at the University of North Dakota in partnership with W. L. Gore & Associates, Inc. and DOE's NETL.
- The design used alternating lanes of pulse-jet filters and ESP plates and RDEs in the second, third, etc. fields in an existing ESP. This is shown in the next two slides.
- Baffles kept flue gas exiting the first ESP field from directly impinging on the pulse-jet filter bags.
- A full-scale demonstration of this technology took place at Otter Tail's Big Stone plant in 2002 – 2004.


Advanced Hybrid Particulate Collector



Top View of Tubesheet

Advanced Hybrid Particulate Collector

Advanced Hybrid Operation



Fine Particle Agglomerator

- Development work by Environmental Elements Corporation (now Clyde Bergemann EEC) began in 1994 with a DOE SBIR project.
- The concept was to utilize laminar flow in a middle field of an electrostatic precipitator (ESP) to promote contact of fine sub-micron particles with larger particles such that the fine particles form agglomerates with the larger particles.
- These agglomerates would then be easily removed in the remaining portion of the ESP.
- The FPA consists of closely spaced parallel collecting and high voltage plates operating below corona onset.


Fine Particle Agglomerator

- A successful demonstration of the FPA technology occurred in 1998 at WE Energies Presque Isle Station.
- The second of three ESP fields for one of the 90 MW units was replaced with the FPA (9' long by 30' high).
- This unit normally used an SO₃ injection system for ESP performance enhancement. To determine a baseline condition, the SO₃ system was turned off. In that situation the nominal opacity was 15%.
- With the FPA, at full load, and no SO₃ injection, the opacity ranged from 5.5 to 7.6%. At half load, 0.6%.
- The migration velocity improvement factor ranged from 1.5 to 2.0, equivalent to increasing the SCA by 50%+.

Indigo Technologies Bi-Polar Agglomerator

- The Bi-Polar or Indigo Agglomerator is a unique, patented technology developed by Indigo Technologies of Australia.
- It treats the ash prior to entering the electrostatic precipitator and uses electrostatic forces to attach the fine particulate to larger, more easily collected, particles.
- The key to this technique is the Bi-Polar Charger which charges half of the ash positively and the other half negatively.
- Fine negatively charged particles are mixed with large positively charged particles, and vice versa.

Bi-Polar Agglomerator



Bi-Polar Agglomerator - Outlet



Bi-Polar Agglomerator

- Pilot tests took place in Australia and the United States.
- Tests in the United States took place at Mississippi Power Company's Plant Watson in Gulfport, MS.
- It is a 250 MWe plant with two precipitators each treating half of the boiler output. The bi-polar agglomerator was installed to treat the full flow to one of the two side-by-side ESPs.
- Opacity monitors were installed in the outlet of each precipitator.
- Testing took place during firing of several American and foreign coals.

Bi-Polar Agglomerator – Plant Watson

<u>MEASUREMENT</u>	<u>A Side</u>	<u>B Side</u>
• OPACITY %	15	4
• PARTICULATE		
• Grains/Act. Cubic Ft.	0.012	0.0066
• Pounds per Million BTU	0.0382	0.0231
• FLOW		
• Actual Cubic Ft/Min	408,718	450,700
• GAS TEMPERATURE (F)	276.3	272.6

Bi-Polar Agglomerator

- Today Indigo Technologies has installed 13 of their Fine Particle Control Systems, incorporating the Bi-Polar Agglomerator, on eight power plants in the United States, Australia, and China.

COHPAC I and COHPAC II

- COHPAC is an abbreviation for **CO**mpact **H**ybrid **PA**rticulate **C**ollector.
- It is a patented technology developed by EPRI in the early 1990s.
- **COHPAC I** refers to the concept of a stand-alone pulse-jet baghouse inserted downstream of an existing poorly performing ESP to polish the flue gas prior to the scrubber or stack. This can eliminate the need for a costly refurbishment of the ESP.
- Because most of the particulate matter is removed in the ESP, the pulse jet baghouse can operate at higher A/C ratios and be smaller in size. A/C ratios can be 6 to 8 ft/min compared to normal 4 ft/min values.

COHPAC I and COHPAC II

- Commonly various PPS felted fabrics are used for utility applications of this technology. 7 denier PPS filaments are used today in felt preparation. Felts made from these larger fibers provide adequate filtration and lower pressure drops values.
- There are three large installations of this technology currently in service: Luminant's Big Brown Station, Alabama Power's Gaston Generating Station, and WE Energies' Presque Isle Station.
- The **COHPAC II** technology does not use a separate baghouse, but replaces the rear ESP field with a compartment of filter bags and a redirected outlet plenum.

COHPAC I and COHPAC II

- Testing of the COHPAC II concept occurred at a pilot test facility installed by EPRI at Alabama Power's Plant Miller Unit 3 in the mid-1990s.
- There are no full-scale commercial installations of the COHPAC II technology.

COHPAC I[®]




Illustration provided by EPRI

COHPAC II





Illustration Provided by
EPRI

Gaston COHPAC Installation

- Gaston Units 1, 2, 3, and 4 are identical moderate sized units. Units 1 and 2 share a common stack flue, as do Units 3 and 4. To improve opacity and eliminate the cost of sodium addition for the hot-side ESPs, COHPAC baghouses were added to Units 2 and 3.
- The baghouses were installed in the old, unused, cold-side ESP casings. An additional 12 feet of length was added to each casing to accommodate the bag modules.
- The Unit 3 baghouse started up in January 1997; the Unit 2 baghouse started up in June 1999.



**Side-View
E.C. Gaston
COHPAC System**

ESP to FF Conversion Downstream of Hot-Side ESP.



E. C. Gaston COHPAC Baghouse Tubesheet



E. C. Gaston Unit 3 COHPAC Baghouse Casing and Pulse Reservoirs

Gaston COHPAC Baghouses

- Each casing contains two compartments with a bypass duct between the compartments.
- The bypass duct can handle a full-load bypass, if necessary.
- The low-pressure/high volume pulse-jet cleaning system is the Howden/Carter-Day design with rotating pulse manifolds and filter bags arranged in concentric circles.
- Each of the four bag modules per casing has 544, 23-foot long filter bags arranged in 14 concentric rows.
- Each rotating pulse manifold has two arms to clean the even and odd rows.
- The pulse pressure has been set at 10 or 11 psig.

Gaston Baghouse Performance

- The Unit 3 baghouse has been in operation for 13 ½ years.
- The Unit 2 baghouse has been in operation for 11 years.
- The air-to-cloth ratios have ranged from 4 ft/min (low load) to 9 ft/min (full load).
- Flange-to-flange pressure drop values have ranged from 1 to 7 in. H₂O over the same load range.
- Pulse frequencies around 0.15 to 0.20 p/b/h have been common with the 7.0 denier PPS felts. They were somewhat higher with the 3.0 and 2.7 denier felts – 0.4 to 0.7 p/b/h.

Gaston Baghouse Performance

- Four sets of bags have been installed in the Unit 3 baghouse. Average bag life has been about 32,000 hours. The last set was installed in Spring 2008.
- Bag lives have been somewhat shorter on the Unit 2 baghouse (21,000 hours). Its fifth set of bags were installed in February of this year.
- Baghouse emissions have typically been very low, averaging about 0.005 gr/sdcf, with excursions coincident with bag failures episodes.
- Average opacity values have been halved with the operation of the COHPAC baghouses and sorbent addition upstream of the ESPs has been eliminated.

Gaston Baghouse Performance

- Compared to the average of the two years previous to COHPAC installation on Unit 3, in the 13.5 years since the opacity has declined an average of 53%, even while the average load for Units 3 and 4 has increased 16%.
- Compared to the average of the two years previous to COHPAC installation on Unit 2, in the 11 years since the opacity has declined an average of 44%, while the average load for Units 1 and 2 has increased 4%.

Early Unit 3 bag failures in the upstream bundles were primarily caused by bag-to-bag abrasion resulting from flue gas sweeping between the bag bundle and the compartment walls. The installation of restraining rings, as shown below, greatly reduced the problem.



TOXECON I[®]

- TOXECON I[®] is an EPRI-patented process that involves the injection of sorbent materials upstream of a COHPAC I[®] baghouse to adsorb HAPs, most commonly, mercury.
- The use of the COHPAC I[®] technology allows the recycling of the dry sorbent material that is mixed with a minimal amount of fly ash, thereby increasing the cost efficiency of the overall process.
- This process is illustrated in the following slide.

TOXECON I[®]




Illustration provided by EPRI

WE Energies TOXECON I[®]

- The TOXECON I process has been tested at pilot scale at a number of power plant facilities.
- One of the major full-scale applications of TOXECON I is located at WE Energies Presque Isle Power Plant located near Marquette, Michigan.
- Baghouses were installed downstream of the hot-side ESP and APH on three 90-MW units that fed to a common stack. The units burn PRB coal.
- The installation and testing program were part of a \$54 million DOE Demonstration.
- Flue gas was rerouted through the baghouses in January 2006.
- Many parametric test programs have taken place.

WE Energies TOXECON I[®]

- Each baghouse has ten compartments. Each compartment has two 324-bag bundles.
- Each bag bundle is arranged in an 18 x 18 array. High pressure/low volume on-line cleaning is used.
- The total gas volume cleaned is 1.08 million acfm.
- The nominal air-to-cloth ratio is 5.5 ft per minute (gross).
- Preliminary performance data indicated excellent mercury removal.
- Parametric and long-term performance testing continued until 2009.

WE Energies TOXECON I[®]

- 90% mercury removal has been achieved with sorbent injection rates of 1.0 lb/h with Norit LH and 1.7 lb/h with Norit Hg.
- Bag cleaning rates range from 0.6 p/b/h with one unit in service to 0.2 p/b/h with all three units in service.
- Ash is pulled from the hoppers every four hours.
- Hopper wall temperatures are maintained below 300 degrees F.
- There have been several O&M issues that have been addressed since startup.
- These include spontaneous combustion, ash/PAC handling, duct corrosion, and bag life.

WE Energies TOXECON I[®]

Spontaneous Combustion

- Changes in operation have successfully prevented recurrence of problems
 - Complete emptying of hoppers
 - Minimizing residence time of ash/PAC in hoppers
 - Lower set point for hopper heaters
 - Minimize injection rate of sorbent
- CO monitors were tested in several hoppers
- The tests demonstrated that these types of monitors were not adequately sensitive to provide acceptable warning of combustion.

WE Energies TOXECON I[®]

Material Handling Issues

- The ash silo wet un-loader caused significant problems
 - There were excessive fugitive dust occurrences during startup periods
 - This required extensive modifications
 - This included adding an enclosure around the truck loading station to contain fugitive ash.

WE Energies TOXECON I[®]

Duct Corrosion

- Wall loss up to 19% in localized areas
- Expansion joint frames
- Diverter damper seals
- Possible causes include:
 - Increase of SO₃ concentrations across baghouses
 - Dead-ended ducting can create conditions below the acid dewpoint under certain operating conditions

WE Energies TOXECON I[®]

Bag Life

- Bag testing indicated that the original PPS bags had reached their end of life (3 years)
- The utility had expected considerably longer life
- A complete set of replacement bags were ordered
- There were no actual bag failures
- End of life was determined by Mullen Burst Strength Tests

Additional TOXECON I[®] Installations

- American Ref-Fuel, SEMASS Waste-to-Energy Combustors Units 1 & 2
 - 2 x 25MW Boilers
 - First Full-Scale TOXECON Demonstration
 - System captures Hg, Dioxins/Furans and other metals
- WE Energies, Presque Isle Units 7, 8 & 9
- PSEG Bridgeport Harbor Unit 3
- PSEG Mercer Station Units 1 & 2
- Dynegy Vermillion Station Units 1 & 2
- Georgia Power, Plant Scherer 1-4
- LG&E, Trimble County Unit 2

Information provided by ADA

EPRI TOXECON II™ Configuration




Illustration provided by EPRI

Questions?