

REINHOLD ENVIRONMENTAL Ltd.



## **2015 Wastewater-Ash Round Table Presentation**

September 22, 2015, in Charlotte, NC / Hosted by Duke Energy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

*Trusted for experience. Preferred for performance.*

# Planning Ahead for Bottom Ash Conversions to ZLD

Tyler Little

Allen-Sherman-Hoff

© 2015 DIAMOND POWER INTERNATIONAL, INC. ALL RIGHTS RESERVED. This document is the property of DIAMOND POWER INTERNATIONAL, INC. (DPII) and is "CONFIDENTIAL AND PROPRIETARY" to DPII. Recipient and/or its representatives have, by receiving same, agreed to maintain its confidentiality and shall not reproduce, copy, disclose or disseminate the contents, in whole or in part, to any person or entity other than the Recipient and/or Recipient's representatives without the prior written consent of DPII.

ISO 9001:2008 Certified





# Outline


---

- Review of current regulatory landscape for bottom ash (BA)
- Effect of zero discharge on water balance
- Effect of zero discharge on water quality
- Developing a robust system design



# Current Landscape

Over 65% of coal generating units operate exclusively wet BA transport systems (from EPA 2009 survey)





# Final CCR Ruling

---

- Existing surface impoundments (ash ponds)
  - Location restrictions
  - Groundwater protection standards
  - Structural requirements
  - Fugitive dust control
  - In-flow controls
  - Record keeping
- Existing impoundments may continue to operate through useful life provided they are not “leaking” contaminants into groundwater



# Proposed ELG for BA Transport Water

	Option 3a, 3b or 3		Option 4a
TSS	30 mg/L avg. of daily values for 30 consecutive days	100 mg/L max. for any 1 day	Zero Discharge (ZLD) for >400 MW
Oil and Grease	15 mg/L avg. of daily values for 30 consecutive days	20 mg/L max. for any 1 day	
pH	6 – 9		






# What does ZLD really mean?

---

- Zero discharge from a contained system
  1. Recirculation with ponds
    - No pond overflow
    - Rely on evaporation & rain water controls
  2. Recirculation with tanks or concrete basins
    - Dewatering bins (HYDROBIN<sup>®</sup>)
    - Remote drag conveyors (RSC<sup>2™</sup>)
    - Dewatering basins
- Blowdown is not an option




# Precipitation vs. Evaporation




<http://mi.water.usgs.gov/projects/WaterSmart/background.html>



# HYDROBIN<sup>®</sup> System



# Remote Submerged Chain Conveyor (RSC<sup>2</sup><sup>TM</sup>)





# Potential Streams in BA ZLD System

---

- BA transport water (1,500 – 3,500 GPM/line)
- Ash hopper service water (300 – 500 GPM/unit)
- Transport water for other materials
  - Mill rejects
  - Economizer ash
  - Air heater ash





# Recirculated Streams

---

- Intermittent flows
  - Bottom ash Hydro-ejector (High Pressure)
  - Hopper & seal trough flushing (HP)
  - HYDROBIN® screen backwash (HP)
  - Ash hopper fill (Low Pressure)
- Continuous flows
  - Hopper wall refractory cooling (LP)
  - Hopper & seal trough make-up (LP)
  - RSC<sup>2</sup>™ chain wash (LP)
- Miscellaneous system sumps
  - Dewatered ash pile runoff





# System Water Balance

---

- Water losses
  - Ash hopper evaporation (5 – 15 GPM/unit)
  - Retained moisture in dewatered ash (2 – 20 GPM/unit)
  - Hopper leakage?
  - Natural evaporation (<1 GPM yearly average)
- Water additions
  - Seal water for pumps (20 – 100 GPM total for all pumps in system)
  - Rain if not in building (<1 GPM yearly average)





# Water Surge Volume

---

- ZLD creates an issue for maintenance
- Need available volume in system to accommodate draining equipment for maintenance
  - HYDROBIN<sup>®</sup> tanks or RSC<sup>2™</sup> volumes
  - Ash hopper volumes
  - Piping volumes
- Overflow from settling tank goes to surge tank/basin
  - Can be several hundred thousands of gallons
  - Consider dual 100% capacity surge tanks/basins



# HYDROBIN<sup>®</sup> System with Surge Tank





# RSC<sup>2</sup><sup>TM</sup> Building Enclosures

---

- Need covering for rain protection over dewatered ash piles
- Equipment is designed for outdoor service
- Considerations for conveyor enclosure
  - Freeze protection
  - Does it increase likelihood of good maintenance practices at your site?
  - Overhead lifting access
  - Cost
    - Number of conveyors, overflow water quality, and storage bunker capacity dictate size of building



# RSC<sup>2</sup><sup>™</sup> Building Enclosure




# Dewatered Ash Pile




# Water Quality in ZLD

- Scale formation
- Corrosion
- Total suspended solids (TSS)



# Water Quality – Scale Formation

- Common with sub-bituminous coals
  - Usually calcium carbonate or aluminum hydroxide
- Factors affecting scale formation
  - Dissolved solids concentration
    - Concentration increases with water recirculation
  - pH
    - $\text{CaCO}_3$  precipitates at high pH
    - Sub-bituminous slurry samples pH = 10 – 12
  - Temperature
    - $\text{CaCO}_3$  solubility decreases with temperature (more dissolved solids precipitate as scale)
    - Recirculation systems will run a little higher water temperature (90 – 110 F)
  - Fouling due to deposition of suspended solids
    - High suspended solids increase scale potential by increasing number of nucleation sites



<http://www.ldeo.columbia.edu/~sanpisa/OceanSed%20project/class%20project/caco3phsol.JPG>





# Water Quality – Scale Formation


---

- Controlling scale formation
  - pH adjustment
    - Keep pH below critical value for precipitation
    - May not be successful long term due to continual buildup of dissolved solids
  - Scale inhibitors
    - Polymers attach to crystals to inhibit growth



# Water Quality – Corrosion

- High sulfur coals can produce low pH (4 – 6)
- Low sulfur coals tend to produce high pH (10 – 12)
- Largely depends on how much makeup water is added to system
- Wet/dry interfaces most susceptible
  - Overflow weirs and trough
  - Dewatering incline
- Acid or lime injection can be used





# Water Quality – Suspended Solids


---

- Impact of high overflow TSS
  - Erosive wear
    - Pumps
    - Nozzles
  - Sludge accumulation
    - Seal water troughs
    - Effluent basins
  - Fouling
    - Pipes
    - Pump intakes



# Overflow TSS – A Performance Guarantee

To Achieve Average Overflow of 400 PPM






# What Happens to Fines in Overflow Water?

---

- When not pulling BA, flow rate drops significantly and fines begin to settle in effluent basin
- >90% of fines will settle out in 3 hours under these conditions
- Sludge accumulation can be hundreds of cubic feet per day
- Agitation to keep solids in suspension will require large amounts of energy for the large volumes in these basins




# Sludge Accumulation



# Surge Volume Clean-out

- Elevated steel tank
  - Provides automated clean-out
    - Sludge pumps can be high maintenance
  - Need intermediate effluent sump for RSC<sup>2</sup><sup>™</sup> due to elevation
    - Some material will still settle in sump
- In-ground concrete basin
  - Periodic cleanout with excavation equipment
  - Optional sloped floor drive-in design for clean-out
    - Footprint can be large



# Elevated Steel Tank Clean-out





# Equipment wear

---

- High TSS accelerates wear
  - Pumps
    - Are existing pumps rated for high TSS?
  - Nozzles
    - Degrading Hydro-Ejector performance





# Developing a Robust System Design


---

- A well-designed system requires audit of existing system
  - Flow rates
  - Current operational practices
  - Water chemistry
  - Ash material properties



# Ash Material Properties

- Bulk density
    - Affects volumetric accumulation
    - Affects transport rates
  - Compacted density
    - Affects structural calculations
  - Particle density
    - Affects particle settling
  - Cohesive strength
    - Affects chain loading and pull requirements for RSC<sup>2</sup><sup>™</sup>
  - Particle size distribution
    - Affects particle settling
    - Affects dewatering
- By far the biggest impact on equipment size




# Sensitivity to Particle Size

- Fine vs. coarse material can cause:
  - 2 – 3x more chain pull force
  - 3 – 5x surface area for equivalent overflow TSS
  - 50% higher dewatered moisture content



# Sampling

- To get samples with representative particle size distribution, the BA slurry must be sampled
  - Scooping solids from a pond will not provide this
- Slurry samples have more fines than pond samples
- Bottom ash is finer than most people think





# Summary

---

- CCR rule will force closure of some impoundments
- New ELGs may force zero discharge systems for BA transport water
  - For most sites this would mean operation without ponds
- Water balance becomes important since rule would restrict system blowdown
  - A careful review of existing and new streams is necessary
  - Water addition is easy. Discharging water becomes difficult.





# Summary Continued

---

- Water quality becomes a bigger concern in a contained system with more mechanical equipment
  - Prepare for water chemistry control
  - Consider impact of high overflow TSS and effect on O&M costs
- Develop a robust design by doing front-end homework
  - Audit existing system for operational practices, flow rates, ash properties, etc.





---

# Thank You

