

REINHOLD ENVIRONMENTAL Ltd.



2015 Wastewater-Ash Round Table Presentation

September 22, 2015, in Charlotte, NC / Hosted by Duke Energy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.



2015 Wastewater-Ash
Conference

**Weighing the Economics of
Options for Converting to Dry
Ash Disposal**


Michael Roush, PE, MBA

September 22, 2015




Agenda

- ▶ Basic Bottom Ash Handling
- ▶ Available Technologies
- ▶ Case Studies
- ▶ Conclusion




Typical Sluice System



Local/Underboiler System



Remote System




Available Technologies

► Underboiler Technologies

- Underboiler Drag Chain Conveyor
- Pneumatic Conveying System
- Dry Belt/Tray Conveying System
- Vibratory Ash Conveyor

► Remote Technologies

- Remote Drag Chain Conveyors
- Remote Dewatering Bins
- Dewatering/Settling Basins




Local Drag Chain Conveyor

Advantages

- ▶ Proven Reliability
- ▶ Hundreds of installations
- ▶ Robust Design
- ▶ Low Cost

Disadvantages

- ▶ Extended installation outage
- ▶ Large footprint required at bottom of boiler
- ▶ Closed cooling loop may be needed



Bottom Ash Conversion

Major Technologies Available


Pneumatic Bottom Ash System

Advantages:

- ▶ Completely dry system
- ▶ Local or remote storage silo
- ▶ Piping more easily routed than conveyors

Disadvantages:

- ▶ Cost
- ▶ Major demolition
- ▶ Longer outage
- ▶ Higher O&M cost (Pipe Wear)
- ▶ Permitting Concerns
- ▶ Only PC boilers



Bottom Ash Conversion Major Technologies Available


Dry Belt / Tray Conveying

Advantages:

- Completely dry system
- Local or remote storage silo

Disadvantages:

- Cost
- Boiler space requirements
- Major demolition
- Longer outage
- Only PC boilers
- Permitting Concerns



Bottom Ash Conversion

Major Technologies Available


Vibratory Conveying

Advantages:

- Completely dry system
- Local or remote storage silo

Disadvantages:

- Cost
- First of a kind in power market
- Boiler space requirements
- Major demolition
- Longer outage
- Only PC boilers
- Permitting Concerns



Remote Drag Chain Conveyor

Advantages

- ▶ Minimal outage & demo
- ▶ Minimal impact on boiler footprint
- ▶ Fully redundant system possible
- ▶ No water discharge



Disadvantages

- ▶ High Capital Cost
- ▶ Regulatory uncertainty (ELG)
- ▶ Aging sluice system remains a part of the system
- ▶ Distance from the plant makes O&M difficult
- ▶ Manual loading of ash
- ▶ Potential risks associated with TSS carryover
- ▶ New application of a technology



Dewatering Bin System

Advantages

- ▶ Minimal outage & demo
- ▶ Minimal impact on boiler footprint
- ▶ No water discharge
- ▶ System loads directly to truck

Disadvantages

- ▶ High Capital Cost
- ▶ Maintenance intensive with poor history
- ▶ Chemical addition required
- ▶ Regulatory uncertainty (ELG)
- ▶ Aging sluice system remains a part of the system
- ▶ Distance from the plant makes O&M difficult
- ▶ Potential risks associated with TSS carryover



Settling Basin Option

Advantages

- ▶ Minimal outage & demo
- ▶ Minimal impact on boiler footprint
- ▶ Fully redundant system
- ▶ No water discharge
- ▶ Low Cost
- ▶ Few moving parts
- ▶ Large volume for extended ash storage

Disadvantages

- ▶ Short track history
- ▶ Chemical addition may be required
- ▶ Regulatory uncertainty (ELG) with excess water
- ▶ Aging sluice system remains a part of the system
- ▶ Distance from the plant makes O&M difficult
- ▶ TSS carryover risks
- ▶ Large footprint
- ▶ Ability to dewater the ash
- ▶ Potential for double handling
- ▶ Loadout to trucks
- ▶ Winter freezing issues with slope



Case Study #1

- ▶ 1 - 750 MW PC Boiler
- ▶ Located in Northern Midwest
- ▶ Bottom Ash – Sluicing System
- ▶ Fly Ash – Dry Fly Ash and Waste Ash Handling
- ▶ Pond Closures needed (CCR and ELG)




Case Study #1 (750MW PC Boiler)

► Technologies Considered

- Pneumatic Bottom Ash System
- Local Drag Chain Conveyor
- Remote Drag Chain
- Settling/Dewatering Basins

► Ruled Out

- Dewatering Bins
- Vibratory Conveyors
- Dry Belt Conveyors



Case Study #1 (750MW PC Boiler)

▶ Local Drag Chain Conveyor Drivers

- Plant preference for underboiler technology
- Conveyor angle skewed
- Tight fit around pulverizers
- Lowest cost option
- Plant familiarity with system

▶ Decision Makers

- \$15MM
- 6-8 week outage needed
- Outage Schedule does not sync with CCR Rule
- Pulverizer maintenance concerns

▶ NOT CHOSEN



Case Study #1 (750MW PC Boiler)

▶ Pneumatic System Drivers

- Plant preference for underboiler technology
- System navigated well around pulverizers
- No water usage
- Higher Cost than other underboiler option
- Pipe Wear
- Requires a new silo

▶ Decision Makers

- \$25MM
- 6-8 week outage needed
- Outage Schedule does not sync with CCR Rule
- Permit concerns

▶ NOT CHOSEN

Case Study #1 (750MW PC Boiler)

▶ Settling Basin Drivers

- Far from plant
- No pulverizer access concerns
- Only short outage required
- Low Cost
- Closed Loop system not common or well proven

▶ Decision Makers

- \$20MM – 3 Cell System
- Outage Schedule syncs with CCR Rule
- Low Cost
- Maintenance concerns, winter concerns, TSS concerns

- ▶ **NOT CHOSEN** due to lingering concerns about how to handle winter months, double handling, and operator intensive operations



Case Study #1 (750MW PC Boiler)

► Remote Drag Chain Conveyor Drivers

- Far from plant
- No pulverizer access concerns
- Only short outage required
- High Cost
- New application of this technology

► Decision Makers

- \$35MM – Dual Conveyor, \$25MM Single Conveyor
- Outage schedule syncs with CCR Rule
- High Cost

► CHOSEN due to outage requirements and lower overall maintenance concerns than the settling basin option



Case Study #2

- ▶ 150MW & 50MW PC Boilers
- ▶ Located in Northern Midwest
- ▶ Bottom Ash – Sluicing System
- ▶ Fly Ash – Dry Fly Ash and Waste Ash Handling
- ▶ Pond Closures needed (CCR, ELG and State)



Case Study #2 (50MW & 150MW PC Boilers)

► Technologies Considered

- Pneumatic Bottom Ash System
- Remote Drag Chain Conveyors
- Settling/Dewatering Basins

► Ruled Out

- Dewatering Bins
- Vibratory Conveyors
- Dry Belt Conveyors
- Underboiler Drag Chain Conveyor

Case Study #2 (50MW & 150MW PC Boilers)

▶ Settling Basin Drivers

- Only short outage required
- Closed Loop system not common or well proven
- Would have to clean close ponds to make space

▶ Decision Makers

- \$9MM
 - Available land
 - Floodplain
 - Maintenance concerns, TSS concerns, public perception
- ▶ NOT CHOSEN due to concerns with cost, floodplain concerns, land available, and familiarity with other technologies.



Case Study #2 (50MW & 150MW PC Boiler)

▶ Remote Drag Chain Drivers

- Only short outage required
- High Cost
- New application of a technology

▶ Decision Makers

- \$12MM – Single Conveyor
- Outage Schedule
- High Cost

▶ NOT CHOSEN due to overall high cost



Case Study #2 (50MW & 150MW PC BoilerS)

▶ Pneumatic System Drivers

- Plant already has pneumatic on two units
- No water usage
- Pipe Wear
- Requires a new silo (footprint)

▶ Decision Makers

- \$9MM
- 8 week outage needed
- Outage Schedule already in place

▶ CHOSEN due to low cost and system familiarity

Case Study #3

- ▶ 1 - 750 MW PC Boiler
- ▶ Located in Northern Midwest
- ▶ Bottom Ash – Sluicing System
- ▶ Fly Ash – Dry Fly Ash and Waste Ash Handling
- ▶ Pond Closures needed (CCR and ELG)



Case Study #3 (750MW PC Boiler)

► Technologies Considered

- Local Drag Chain Conveyor
- Remote Drag Chain Conveyors
- Dewatering Bins

► Ruled Out

- Vibratory Conveyors
- Dry Belt Conveyors
- Settling Basins

Case Study #3 (750MW PC Boiler)

▶ Remote Drag Chain Drivers

- Far from plant
- Only short outage required
- High Cost
- New application of a technology

▶ Decision Makers

- \$35MM – Dual Conveyor
- Outage Schedule syncs with CCR Rule
- High Cost

▶ NOT CHOSEN due to higher cost, proximity to plant and familiarity with other technologies



Case Study #3 (750MW PC Boiler)

▶ Remote Dewatering Bin Drivers

- Far from plant
- Only short outage required
- High Cost
- Operations History with technology

▶ Decision Makers

- \$35MM – Dual Train System
- Outage Schedule syncs with CCR Rule
- High Cost

▶ NOT CHOSEN due to higher cost, proximity to plant and past history with this technology

Case Study #3 (750MW PC Boiler)


▶ Local Drag Chain Conveyor Drivers

- Plant preference for underboiler technology
- Lowest cost option
- Plant familiarity with system

▶ Decision Makers

- \$15MM
- 6-8 week outage needed
- Outage Schedule syncs with CCR Rule

▶ CHOSEN due to low cost, familiarity with technology and already planned outage schedules



Questions???