

REINHOLD ENVIRONMENTAL Ltd.



2015 Wastewater-Ash Round Table Presentation

September 22, 2015, in Charlotte, NC / Hosted by Duke Energy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

Zero Liquid Discharge System at Stanton Energy Center

Challenges and Solutions

Presented By

Eric Costello, PE – Orlando Utilities Commission

Dean Ritts, PE, CEM – Ritts Sustainable Engineering, LLC

OUC SEC ZLD Background

- History of OUC and SEC
 - Formed at the turn of the 20th Century
 - Purchased by citizens of Orlando in 1922
 - Authority as electric & water utility in 1923 by State
 - OUC operates as Commission
- Stanton Energy Center 1 and 2 Coal Units
 - Each has a gross rating 460 MW
 - Cycled at night

OUC SEC ZLD Background

- What does it mean to have a ZLD system?
 - No process water leaves the site
 - Managing water is essential to operations
 - Recent trends in unit loads and rainfall
 - ZLD site – integrated water management
 - Complimentary alternatives for CCR

Challenge - What changed?

Over Time from 2003:

- Addition of Combined Cycle Units;
- Change in Fossil fuel mix;
- Significant storm events;

Resulting in:

Decreased capacity to cost effectively maintain a zero liquid discharge system when operating cycling coal-fired units

Combined Cycle Units – SEC A and SEC B




RELIABLE • AFFORDABLE • SUSTAINABLE

OUC SEC ZLD Background

- Main components of the ZLD at SEC?
 - Waste Water Ponds
 - FGD Make-up
 - Brine Plant – mechanical vapor compressor & crystallizer
- Successful ZLD Operation Requires
 - Storage Management
 - Re-use & Recycling

Site Plan – OUC SEC ZLD System



FGD System Evaporation – Full Load



RELIABLE • AFFORDABLE • SUSTAINABLE

Brine Plant Blowdown SEC 1&2 & SEC A & SEC B



RELIABLE • AFFORDABLE • SUSTAINABLE

Brine Plant




RELIABLE • AFFORDABLE • SUSTAINABLE

Solutions needed

- Reduce short term impact of managing water – low cost solutions, maintain zero liquid discharge
- Long term strategy to manage water to maintain ZLD system cost effectively
- Integrate CCR management requirements if possible
- Process optimization for solids process management, Cl control in scrubbers, and storm water management
- Solution must reflect Engineering, Environment, and Economics

Approach – Five Steps to Success



Site Survey - Step 1

- Three day focused site-survey
 - Opening meeting and preliminary review of process and goals
 - “Walk-about” for data collection and interviews with operators
 - Close-out meeting to present survey findings to project team
- Review Data, create tools, develop findings

Site Survey Results - Step 1

- Tools Developed from Step 1
 - Engineering Water/Wastewater Balance
 - Equilibrium Chemistry Model for Identified Key Processes (Cooling towers, demineralizers, MVC, etc.)
 - Pond volume flow model – probability of overflow

Site Survey Results (continued)

- Major Findings

- Developed “magic number” of wastewater volume that ideally should be diverted or removed from the Recycle Basin pond every day to allow ZLD to operate efficiently
- Understanding of impact of storm events on recycle basin and ability of one FGD system to keep up: 1 yr. storm event can add 9.1 MG of water to recycle basin
- Large dischargers and large users of water – including “one-offs” like outages (i.e., boiler flush)

Site Survey Results (continued)

- Major Findings
 - Better understanding of water/wastewater chemistry
 - Collection of operators concerns and observations and their solutions
 - Impact of CCR management and need to reduce solids overflow from scrubbers, coal pile runoff, and solids management pad

Solids Management Pad



Opportunities Assessment & Prioritization – Steps 2 and 3

Develop & Prioritize Alternatives to Reduce Water and Chemistry Load on Recycle Basin

Based on:

- Technical Feasibility
 - Impact on problem
 - Operational Feasibility
 - Cost – CapEx/OpEx
 - Impact on Pond Volumes and Probability of Overflow
- Workshops to discuss, select and prioritize
 - Spreadsheet approach to catalogue opportunities

Opportunities Selected for Detailed Study

- Opportunities prioritized by project team in to three categories, high, medium, low
- Fall into four main technical categories:
 - Operational change
 - Mechanical change
 - forwarding systems
 - Chemical change
 - Civil change
 - combinations

Opportunities Selected for Detailed Study

- Re-route demineralizer wastewater to cooling towers
- Boiler blowdown to cooling towers
- Seal pump water
- RO Regen or replace demineralizer with RO
- Reduce Contact water & misc. drains
- **Brine plant capacity available to treat cooling tower and recycle basin**

Opportunities Around FGD Operation

- Importance of FGD Operation Efficiency
- FGD water balance becomes positive (more makeup than needed) at low load
 - Results in low density and high liquid level in absorbers
 - Increased flow to thickeners. Result in overflow of thickener return water tanks

Opportunities Around FGD Operation

- Revise mist eliminator wash logic to adjust wash frequency based on unit load
- Reduce amount of runoff in CCR stack-out areas
- Reduce seal water to recycle pumps
- Poor man's chloride bleed system

ZLD & CCR Management Interface

- Solids Management is critical – keep solids out of recycle basin to:
 - Maintain storage volume
 - Reduce metals and salts in recycle basin increasing opportunities to re-use water around plant
- Considered
 - Conveyor CCR to landfill
 - Rain Cover Over Sludge Area – reduce contact water
 - Pump CCR to landfill

Implementing Opportunities –Step 4

- Implementing Opportunities is a Reiterative and Collaborative Process
- Key Lessons Learned:
 - 1) Importance of Working Groups to Process
 - 2) Continue to review data and question assumptions: it yields new opportunities
 - 3) Don't throw away opportunities

Economics of Implementing Opportunities

- Risk/reward
- Economics
 - \$/gal for treating with brine plant
 - \$ to investigate sending small amount to cooling towers – became too risky to brine plant and condensate tubes cooling towers
 - \$/gallon for treating with RO system on site

Temporary Measures – RO at Recycle Basin



RELIABLE • AFFORDABLE • SUSTAINABLE

Results Review and Status – Step 5

- Adjust the plan as needed – blend recycle basin water option for example – considered later
- Flow meters will be installed
- Training and follow-up

Next Steps

- New Recycle Pond Construction
- Boiler Blowdown Forwarding System
- Vacuum filter exhauster and vacuum filter filtrate pump re-use
- Neutralization Basin water re-use – pump back to Unit 1 or Unit 2 cooling tower basin

Neutralization Basin



RELIABLE • AFFORDABLE • SUSTAINABLE

Conclusions

- Five Step Approach to develop a long term strategy to manage water to maintain ZLD system cost effectively
 - Survey, Opportunities Assessment, Prioritize, Implement, Evaluate
- Integrate CCR management requirements if possible
- Solution must reflect Engineering, Environment, and Economics
- Process optimization for solids overflow management and Cl control in scrubbers

Discussion