

REINHOLD ENVIRONMENTAL Ltd.



**2014 APC Round Table  
& Expo Presentation**

July 14-15, 2014, in Louisville, KY / Hosted by LG&E/KU

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

# O&M Issues DSI Systems Startup, Shutdown & Cycling Loads

Tony Licata – Licata Energy  
Curt Biehn – Mississippi Lime

**APC Roundtable July 14, 2014**  
**Workshop 7**

# EPA Requested Comments on Proposed New Rules Startup-Shutdown-Maintenance (SSM)

- Request published on 6/25/13 based on rules proposed 12/30/12
- Reopened comment period limited to 3 questions
- Institute of Clean Air Companies (ICAC) submitted comments on 8/26/13 addressing
  - SCRs & SNCR
  - ESPs
  - Baghouses
  - Wet and Dry FGD
  - DSI & carbon injection

# O&M Issues Coal Fired Plants

- Startup – Shutdown Rules
- Start averaging time using a default electrical production
  - 25% of nameplate capacity plus 3 hrs. or
  - the start of electricity generation plus 6 hrs., whichever comes first;
- Other Industry Challenges Cycling Loads
- “Green” Energy and gas price: coal plant cycling
  - Shutdowns: hours to a few days
- Low load operations
- Improved heat rate for CO<sub>2</sub> Rule

# DSI Challenges

- How soon can we turn on or turn off on hydrated lime & carbon systems.
- Prevent deposits forming in ductwork.
- Sorbent contact with acid gases/Hg at low flow conditions -**mass transfer**
- Does the chemistry work at lower temperatures seen during startup/shutdown?
- Contact time
- Impacts on balance of plant

# What Can We Do?

- Modeling - most modeling for flow distribution and deposition done at full load conditions.
- Need to model at low flow conditions
- Inspections of ductwork after cycling operations
- Use CEMS when possible to optimize sorbent injection.
- Other
  - Better distribution
  - More frequent tuning
  - Frequent cleaning of catalyst & airheater
  - DSI injection ahead of airheater

# Benefits of DSI Injection During Start/Shutdown and Cycling Operations

- With increased cycling operations we expect to see increased corrosion along the flue gas path. Lime injection could mitigate corrosion that will develop with these operating conditions
- Allow SCRs to startup earlier (lower operating temp.)
  - Startup - Shutdown Conditions
  - Turn on ammonia  $\approx 600$  °F
    - Actual depends on fuel primarily sulfur
  - SCRs are temperature driven – no relationship to MW generation


# Typical SCR Startup & Shutdown

- Startup - Shutdown Conditions
  - Temperature limited by ABS formation that fouls airheater
  - ABS needs  $\text{SO}_3$  and  $\text{NH}_3$
  - Take  $\text{SO}_3$  out and you can start injecting  $\text{NH}_3$  sooner which will result in reducing  $\text{NO}_x$  and being in compliance sooner
  - Inject lime before catalyst or airheater
    - May be able to lower startup temperature from 600  $\longrightarrow$  540 °F

# Benefits of SO<sub>3</sub> Removal prior to the APH


## APH operations

- Eliminate ABS buildup from ammonia slip
- Reduce dP growth over time
- Eliminate outages for cleaning




# Benefits of Pre-APH Removal of $\text{SO}_3$


## Improve Heat Rate/Reduce $\text{CO}_2$ Emissions

- Reduce  $\text{SO}_3$  Dew Point prior to APH
- Reduce operating temperature of APH 

**40°F reduction → 1% heat rate improvement → 1% savings on fuel budget**


- Reduction in  $\text{CO}_2$  emissions 
  - 1 lb coal → 2.5 lb  $\text{CO}_2$

# SO<sub>3</sub> Acid Dew Point Curve




# Warm Startup

Graph 2- U1 Warm Start Data (Jan 11-12, 2012)



# Cold Startup

Graph 3  
Cold Start Data (Apr. 2012)



# DSI Challenges

- Emissions Control
- Operate over wide range of load conditions
- Can it play a role in heat rate improvement
- “Net” low cost sorbents that minimize impact on other APC equipment performance and ash management

# DSI Design


- Periods of operation, especially for boiler startup, characterized by rapid transient changes in flue gas composition, quantity, temperature, and moisture conditions.
- The problems are aggravated with installation of multiple APC equipment and processes, especially those required to achieve MATs compliance.
- Minimize Sorbent usage
  - Cost
  - Ash
  - Other APC equipment

# Key To DSI Design




- Distribution of sorbent
- Get the sorbent to the pollutant in the flue gas
- Adjustable feed rate – don't overfeed or underfeed
- Modeling
- Mixing
- Maintain Calcium/air ratio in transport pipe and injectors ( $>0.4$  lbs hydrate: lb air)
  - High air (low ratio) -> tendency toward scale
  - Low air (high ratio) -> stay above saltation velocity

# Use of Mixers for Uniform Distribution




# Mixing at Various Loads


Case 1 – 25% Load Design Case  
DSI Duct with Mixers



Case 2 – 50% Load Design Case  
DSI Duct with Mixers



Case 3 – 75% Load Design Case  
DSI Duct with Mixers



# DSI System – Hydrate for SO<sub>3</sub> Control

- Target feed rates established during stack test period
  - Complete load profile, not all at full load
  - Coal sulfur content ranges
- In line monitoring of emissions
  - SO<sub>3</sub> : Breen, SICK, Stack visual
  - SO<sub>2</sub> : CEMS
  - Hg : CEMS (indirect method)


# Start-up and Shut-down Events

- Shut-down
  - Main priority: leave the system ready to run
    - Empty rotary feeder, feed lines, splitter(s), and lances
    - Keep the blower running as long as there is a risk of flue gas passing into the DSI system
    - Follow manufacturer's recommendations
  - Manage inventory in silo and air quality to bin activators
- Start-up
  - Sorbent flow: pollutants present and flue gas flow sufficient
  - Baghouse: bag coating
  - Sorbent Cost < Cost of a Fine


# During Operation Maintain Sorbent Flow and Distribution to Duct

- Handling best practices = high system On Stream Times
  - Consistent flow from silo to rotary feeder
  - Manage conveying air balance with sorbent
  - Optimize convey temperature and moisture content
  - Convey line size, length, and pathway
- Cover the flue gas
  - Effective flow split
  - Lance # and depth
  - Distribution in flue gas
    - In-duct mixers
    - Special lances

# Improved Distribution to Meet HCl MATS




# Longer Residence Time Improves HCl Removal



# Use a Better Sorbent

- Next generation sorbents available
  - Capability for high level ( $> 90\%$ ) pollutant removal
  - Higher costs offset by lower annual usage
- Additional benefits
  - Lower emissions level – like buying insurance
  - Fewer deliveries
  - Less stress on feed system and other APC equipment
    - ESP
    - Particulate
    - Ash disposal
  - Inventory advantages

# High Reactivity Hydrated Lime Allows a Plant to Meet SAM Requirements




# Pre-APH with Hydrated Lime

## Where are We Now?

- Significant testing, retro-fits, and installations in past 3 years
  - Over 35 units (~23 GW)
- Many units have operated with Pre-APH injection of hydrate for over 12 months and multiple outage cycles
- $\text{SO}_3$  is being controlled
- Air preheaters are staying clean

# Hydrated Lime Injection Upstream of APH

## Example of Recognized Improvement



# TVA – Paradise Units 1 & 2

## Benefits from Pre-APH Injection of Hydrate

### Post-APH Injection of Hydrated Lime (Jan '11 – Mar '13)

- Over **570,000 MWh** were lost as a result of air heater fouling from both units

### Pre-APH Injection of Hydrated Lime (Mar '13 – Current)

- **0 MWh** have been lost as a result of air heater fouling
- Have not experienced any APH pluggage attributed to hydrate injection
- Contributing Factors:
  - Air Heater maintenance
  - Combustion Tuning
  - SCR catalyst replacement/ Tuning

# Injection of Hydrated Lime Pre-SCR

## Benefits

- Earlier control of  $\text{SO}_3$
- Longer contact time
- Enhanced mixing

## Concerns

- Fouling of catalyst
  - No signs of deactivation on test conducted to date
- Likely need secondary hydrate injection point downstream of SCR
- Implications of HCl removal on Hg

# Questions & Answers

Tony Licata

Licata Energy & Environmental Consultants, Inc.

345 Concord Road

Yonkers, NY 10710

Phone 914-779-3451

Email [TonyLicataLEEC@aol.com](mailto:TonyLicataLEEC@aol.com)

Curt Biehn

Mississippi Lime

3870 S. Lindbergh Blvd.

St. Louis, MO 63127

Phone 314-543-6309

Email [cbiehn@mississippilime.com](mailto:cbiehn@mississippilime.com)