

Reinhold Environmental Ltd.



2009 APC Round Table & Expo Presentation

July 12-14, 2009, in The Woodlands, TX


All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

Testing the Use of Trona for SO₂ Removal



APC Roundtable Meeting
July 13-14, 2009
The Woodlands, Texas

Connie Senior
Marc Cremer
Dave Wang



Presentation Overview

- A Little History
- A Little Chemistry
- A Little Engineering
- Case Study



A Little History

- Late 1980s-early 1990s, DOE funded development of lower-cost alternatives to wet FGDs
 - Several Duct Injection processes investigated: sodium and calcium sorbents for SO_2 control
 - Clean Coal Technology program at Arapahoe Station demonstrated 70% SO_2 removal with trona injection between APH and FF
- Renewed interest in “moderate” levels of SO_2 removal
 - For example, 2005 at Potomac River showed up to 80% SO_2 removal with trona injection between Economizer Outlet and H-ESP



What is Trona?

- Natural mineral: sodium sesquicarbonate
 - $\text{Na}_2\text{CO}_3 \cdot \text{NaHCO}_3 \cdot 2\text{H}_2\text{O}$
- Green River formation
 - Seams from 600 to 3500 ft. depth
 - 2500 square miles
 - > 100 billion tons
- Rail or truck delivery
- Bulk density: 49 lb/ft³
- Size: 28-50 micron



A Little Chemistry

- Two steps are important for capture of SO_2 (and SO_3):
 1. Calcining
 2. Sulfation



A Little Chemistry

- Two steps are important for capture of SO_2 (and SO_3):

1. Calcining

- At $T > 275^\circ\text{F}$, trona decomposes to form Na_2CO_3 , giving off water and CO_2



- Calcining increases surface area, which improves reactivity
- Higher injection temperature \Rightarrow higher surface area




A Little Chemistry

- Two steps are important for capture of SO_2 (and SO_3):

2. Sulfation

- Na_2CO_3 reacts with SO_2 and SO_3 in the flue gas



- Normalized stoichiometric ratio for SO_2 :
NSR = 2 x moles Na/moles SO_2




A Little More Chemistry

- Trona also reacts with NO_x
 - 10-20% reductions in NO_x have been noted in full-scale applications for SO_2 control
 - NO_2 concentration in stack may increase because of trona




A Little Engineering

- Implementation of trona injection for SO₂ Control




Basic Implementation


- Milling on-line often recommended to improve utilization



Basic Implementation




- Milling on-line often recommended to improve utilization



Source: Arapahoe
CCT program




Storage and Handling



- Transport trona using a dilute-phase pneumatic conveying system
 - Conveying air temperature less than 140°F
 - Relative humidity less than 40%
 - Chiller and a dehumidifier recommended for the conveying air



Storage and Handling




- Well-designed flow splitters, flow straighteners and static mixers in the conveying lines important to avoid plugging.
- Mass flow meters in the conveying lines can monitor flow through lances and help identify plugging




Injection Locations

- Injection at Economizer Inlet




Injection Locations

- Injection at Air Preheater Inlet



Injection Locations

- Injection at Air Preheater Outlet



Balance of Plant Effects

- Neutral or positive effect of trona on performance of cold-side ESPs
- Trona increases sodium content of fly ash
 - Potential issues with sale of ash for concrete manufacture
 - Acceptability for landfill must be evaluated



Duct Injection Costs

- For 50-60% SO₂ reduction
- Capital Cost \$15-25/kW
- O&M Cost \$700-1000/ton SO₂ removed
- Design & Commissioning: under one year

Source: O'Brien & Gere, 2007



Case Study

- Site description
- Summary of trona field test results
- CFD model development
- Model-based optimization



Site Description

- Unit A
 - 86 MW PC, tangentially-fired, 0.7% S
 - OFA, Low-NOx burner mods, SNCR
 - Cold-side ESP
- Unit B
 - 174 MW PC, tangentially fired, 0.7% S
 - Planned OFA, Low-NOx burner mods, SNCR
 - Cold-side ESP
- State environmental regulations (SO_x)
 - $< 0.37 \text{ lb SO}_x/\text{MMBtu}$ by 2009
 - $< 0.26 \text{ lb SO}_x/\text{MMBtu}$ by 2012




Trona Field Testing

- O'Brien & Gere (May 2006 – September 2007)
- Various Sensitivities Investigated
 - Milled and unmilled
 - Injection location (Econ. Inlet, AH inlet, ESP inlet)
 - Injection rate
- Results – Both units
 - Up to 75% reduction at NSR=3.5
 - Best results with injection at economizer inlet
 - Milled performance better than unmilled




Impact of Injection Location

Unmilled Trona – Unit A





Impact of Milling

Unit A – Economizer Inlet



SO₂ Absorption Model Development

- **Trona sulfation kinetics were developed based on packed-bed pilot-scale data**
 - Davis, W.T., Keener, T.C. “Chemical Kinetic studies on dry sorbent”, 1982.
- **Trona particles (Na₂CO₃.NaHCO₃.2H₂O) endure an endothermic decomposition and exothermic SO₂ absorption**





- **The decomposition kinetics are dependent on the Trona particle temperature -- Initiates at 300°F**



Trona Particle Sulfation Kinetics

$$R_{SO_2} = A \cdot P_{SO_2} \cdot S(T) \cdot (1.0 - XB)^2 \cdot \exp(-E/RT)$$

$$R_{SO_2} = m_{SO_2, \max} \cdot dXB/dt$$



Source: Davis, Keener, 1982





Trona Model integration with CFD

- **Integration into REI's CFD model *GLACIER***
 - Solve trona particle momentum, energy equations along the trajectories
 - Determine trona particle decomposition and SO₂ absorption rate
 - Couple the trona decomposition products and SO₂ absorption with gas phase
 - Solve the SO₂ gas phase transport
- **SO₂ removal is determined by:**
 - SO₂ concentration in the flue gas
 - NSR
 - Trona particle coverage
 - Trona particle size (external mass transfer)
 - Gas/particle temperature
 - Residence time




Model-Based Approach

Lower Furnace



Upper Furnace

Backpass




Intelligent Light
FIELDVIEW



Trona Test Lance Configuration

Unit A




- Economizer inlet injection
- 15 lances – 1” and 1-1/4” ID
 - 15 lances for parallel mill operation
 - 9 lances for series mill operation (south duct)



Trona Particle Trajectories

Unit A – Economizer Inlet to AH Inlet




Case 2 – Run 4



Model Verification

Unit A – Economizer Inlet





Flue Gas Velocity and Temperature

Unit A

High down flow velocity near the east wall

Vertical Velocity
25
(ft/sec)
-25

Gas Temperature
720
(°F)
500




Intelligent Light
FIELDVIEW



Sorbent Mass Density

Unit A



Intelligent Light
FIELDVIEW




Reaction Engineering International

APC Roundtable
July 13-14, 2009

SO₂ Concentration

Unit A



Case 2 – Run 4

Intelligent Light
FIELDVIEW



Reaction Engineering International


APC Roundtable
July 13-14, 2009

Simulated Injection Strategies

Unit A


EL 100' : Strategy 1

EL 90' : Strategy 5



EL 100' : Strategy 2


EL 90' : Strategy 6




Simulated Injection Strategies

Unit A

EL 100' : Strategy 3 (24 lances)




EL 100' : Strategy 4 (Diffuser tip)




Results – Injection Strategies

Unit A – Economizer Inlet (NSR=2.5)



Results of Parametric Cases

Unit A



Summary of Case Study

- **Field testing of trona injection for SO₂ control in an 86 MW unit shows:**
 - SO₂ reduction improves when moving injection from the economizer exit to the inlet
 - SO₂ reduction improves when milling from 30 μm to approximately 12 μm D50
 - SO₂ reduction measured up to 74% with NSR = 3.5 with milled trona
- **CFD based model for SO₂ capture by duct injection of trona was developed**
- **Application of model to two coal-fired units shows good agreement with field test results**
- **Prediction of parametric dependencies in the 86 MW shows:**
 - Similar SO₂ removals for injection immediately upstream or downstream of economizer - removal is limited by the trona coverage
 - Potential for 80% SO₂ reduction at NSR=2.5 assuming no distribution constraints
 - 83% reduction is achievable at NSR=3.5 with simulated injection strategies



QUESTIONS?

