

REINHOLD ENVIRONMENTAL Ltd.



2016 APC-Wastewater Round Table & Expo Presentation

July 18 & 19, 2016 in Dearborn, MI / Hosted by DTE Energy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

HDR



O&M Considerations for Treatment of Coal Plant Wastewaters





From the Engineer's Perspective:

1. General considerations for new system design
2. Technology specific considerations



1. General Considerations for New System Design

Plant-Wide Interactions

- Effects on upstream and downstream systems
- Adaptable to changes in fuel
- Effects on fly ash composition and reuse
- Effects on gypsum composition and reuse
- Effects on plant-wide water balance
- WWTP functionality during outages
- NPDES Outfalls



Labor and Staffing

- Operational complexity
- Staff availability
- Training and certifications
- Automation
- Sampling and analysis



Worker Safety

- Equipment/sampling access
- Cranes and hoists
- Fall protection, platforms, stairs
- Confined spaces
- Hazard detection systems
- Chemical storage/feed areas
- Traffic areas



Mechanical Maintenance

- Planned maintenance
 - System capacity during maintenance
- Equipment redundancy
 - Where and when is it valuable
 - It isn't always practical
- Spare parts
 - Similar equipment = shared parts
 - Common and available
 - Online spare or shelf spare?
 - Shelf life



Piping Systems

- Valve location and height
- Valve types
- Actuator types (in 3D model)
- Cleanouts / flush points
- Buried pipe vs. pipe trenches
- Direct bury valves vs. vaults
- Floor drains vs. trench drains
- Winterization




Chemical Areas

- Capital vs. chemical costs
- Storage volumes
- Effects on solids/sludge generation
- Chemistry impacts
- Secondary containment complications
 - Precipitation
 - Confined space
- Effects on building classification
- Temperature effects
- Lime system considerations



Lime Systems; Unloading/Tank Area



- Offloading at <math><12</math> psi, short pipe runs
- May need booster blower
- Size tank or silo for full bulk shipment
- Automation of make-down of lime from silo or super sacks
- Slurry >20% has less settling/mixing
- Design tank for cleanout (side manways, etc.)
- Delivery of pre-made slurry for low consumption applications



Lime Systems; Preventing Line Fouling

- Percent Solids Matters!
 - <15% leads to fouling
 - 20-28% good for recirc loop (4-10 fps)
 - 28-32% used in dead-end piping, and can have lower velocities
- Eliminate stoppages in loops (<28%)
- Optimal line size >2-inch. Install cleanouts, disconnects, flush points
- Use open troughs where possible
- Mineral dispersants (i.e. acrylic acid)
- Consider pre-made slurry

Design for Operations

- Operability is a key design parameter
- Always use 3-D BIM design (Building Information Modeling) when practical.
- Critical to setting aside access space, clearances, etc.
- Milestone meetings throughout design; Invite ops, maintenance, safety folks.



Planning for the Future

- Variable or constant speed motors
- Equipment sizing
 - Pump impeller and motor sizing
 - VFD sizing and pump duty point
- Space
- Tie-in points





2. Technology Specific Considerations

Phys/Chem Treatment

- Multiple applications
 - FGD Wastewater, raw water, misc.
- Chem additives
 - Softening = sludge
 - Polymer overdose
- Clarifiers
 - Standard vs. high rate
 - Cleaning settling tubes/plates
 - Maintaining appropriate sludge bed
- Tertiary filtration
- Dewatering & solids handling



FGD Wastewater: Biological Treatment

- Nitrate and selenium removal
- Several different designs
 - GE ABMet (Fixed bed)
 - Frontier (Fluidized bed)
 - Degremont iBio (Suspended growth)
- O&M concerns
 - Complexity: Maintain biology, nutrients, ORP
 - Sensitivity: Low flow, temp, outages, upsets
 - Off-gassing
 - Re-seeding
 - Solids handling
 - Materials of construction



FGD Wastewater: Chemical Reduction

- A possible alternative to biological treatment for selenium
- Most commonly uses reducing media such as zero valent iron
- Reduces and immobilizes selenium
- Converts nitrate to ammonia. Does NOT denitrify. Must follow with ammonia removal (full denitrification)
- Packed or Fluidized Bed
- Media is disposed, not regenerated. Consider the media usage and operating costs. Pilot test! Plus, handling issues.



FGD Wastewater: ZLD – Brine Concentrator

- Pretreatment is sedimentation for TSS removal, but partial or no softening.
- Stabilize resulting salt slurry with fly ash & other amendments. Affected by fly ash composition.
- Suitable product for landfilling/encapsulation
- Steam for startup
- Complex/lengthy startup & shutdown
- Specialized operator training
- Low TDS water recovery, add minerals prior to reuse



Solidification/Stabilization

- Prevent leaching of solid waste generated from flue gas desulphurization (FGD) unit
- Highly pH-dependent process
- Complications with landfill leachate system?
- Reuse opportunity – using reject fly ash with FGD waste and $\text{Ca}(\text{OH})_2$ retards the leaching of heavy metals¹


¹Qiao et al. 2006



FGD Wastewater: ZLD – Spray Dryer

- Flue gas from boiler to side-stream spray dryer (Mitsubishi WSD, Alstom SDE)
- Two streams in; hot flue gas and FGD purge. No softening or pretreatment.
- Atomizes at high temp in spray dryer (no wetness or corrosion)
- Existing ESP systems remove solids.
- Easy startup, operation, & shutdown
- Operation depends on power block. Outage = no purge treatment
- Effects on fly ash?

Mitsubishi WSD



Reuse of Waste Streams

- High purity RO reject to cooling tower
- Re-circulate process waste streams (if water quality appropriate) to cooling towers
- Re-circulate oil/water separator effluent to cooling towers
- Re-circulate boiler blowdown to cooling towers
- Recycle storm water as service water (rooftop drains, not filtered)



Other Operations Practices

- Condensate polishing for units with intermediate dispatch (frequent starts/stops)
- Continuous water quality monitoring for cooling tower and boiler chemistry control for real-time adjustments



Thank you!



Questions?