

REINHOLD ENVIRONMENTAL Ltd.



2014 NO_x-Combustion Round Table & Expo Presentations

February 10 & 11, 2014, in Charlotte, NC / Hosted by Duke Energy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

The TVA logo consists of the letters 'TVA' in a bold, white, sans-serif font, set against a dark blue square background.

Pre-APH Injection of Hydrated Lime

Update on Recent Testing

Curt Biehn (Mississippi Lime) and Adam Harris (TVA)



Discovering what's possible with calcium

NO_x Conference – Charlotte NC
February 11, 2014

Workshop Overview

- Benefits of Pre-APH Control of SO₃
- Development of the Pre-APH market
- Recent TVA programs
 - Paradise
 - Cumberland
- Recent testing at other Utilities



If you have to control SO_3 ...

You might as well take advantage of it.

- Original DSI systems installed to control SO_3 stack emissions
- Why not
 - Protect equipment and duct work
 - Maintain Air Preheater cleanliness
 - Reduce operating costs

Benefits of SO₃ Removal prior to the APH


Corrosion protection



Benefits of SO₃ Removal prior to the APH

APH operations

- Eliminate ABS buildup from ammonia slip
- Reduce Dp growth over time
- Eliminate outages for cleaning



Two Layer APH with SCR

GAS INLET TEMP = 700F

Plate = 660F




Plate = 640F



Plate = 620F



Plate = 600F




Plate = 260F




Plate = 230F




Plate = 190F






Plate = 160F

Hot Side Gas
320 F


AVG GAS OUTLET TEMP = 290F

Cold Side Gas
260 F




Two Layer APH with SCR and **Increased NH₃ Slip**

GAS INLET TEMP = 700F



Previous Case PLUS Pre-APH SO₃ Mitigation

GAS INLET TEMP = 700F



Hydrated Lime DSI – Impacts on Air Preheater

- Primary Mechanism is SO_3 Reduction
 - Reduction of sticky H_2SO_4 on ash & plates
- Secondary Benefit - Additional particulate for condensation
 - Reacts quickly with any condensed H_2SO_4 to form a dry solid
- Gypsum pluggage has not proved to be an issue.
- No sticky compounds as seen with sodium-based sorbents

Benefits of Pre-APH Removal of SO₃

Improve Heat Rate/Reduce CO₂ Emissions

- Reduce SO₃ Dew Point prior to APH
- Reduce operating temperature of APH




40°F reduction → 1% heat rate improvement → 1% savings on fuel budget

- Reduction in CO₂ emissions
 - 1 lb coal → 2.5 lb CO₂



SO₃ Acid Dew Point Curve



© 2008 Babcock & Wilcox Power Generation Group, Inc. All rights reserved.

Growth of Pre-APH Injection with Hydrated Lime

- Preliminary work
 - Furnace sorbent injection
 - Anti-slagging chemicals in the boiler
 - Brief plant trials
- First tests in 2008 and 2009 – Mississippi Lime
 - One day testing in 2008
 - Successful seven week test in 2009
 - MLC/Southern Co./B&W/Breen/BCSI/Utility
- Subsequent evaluations/conversions starting in 2010



APH after 7 week test, 2009

Pre-APH with Hydrated Lime: Where are We Now?

- Significant testing, retro-fits, and installations in past 3 years
 - Over 35 units (~23 GW)
- Many units have operated with Pre-APH injection of hydrate for over 12 months and multiple outage cycles
- SO₃ is being controlled
- Units are recognizing additional benefits

Test Program Discussion – Hydrated Lime Pre-APH


- Recent results from several plants
- Extended benefits
- Improvement potential from a next-generation hydrated lime
 - High Reactivity Hydrated Lime
 - Designed for ‘high stress’ applications
 - Shorter residence times
 - Rapid, high level SO₃ removal required



TVA Trials – Paradise

- 2 Units – 700MW
- 5 lb/MMBTu coal
- Recuperative Air Heater
- No PPTR or Bag House
- Venturi Scrubber






Typical Injection Set Up




FGT vs. High Reactivity Hydrate

- Both FGT and HR hydrate achieved **94%-98%** reduction in SO_3 concentration across the APH
- FGT injection Rate = 1,000-1,100 lb/hr
- HR injection rate = **750-800 lb/hr**
- Acid dew-point reduction from 300°F to ~275°F




Unit 1 Extended Results

Paradise Unit 1 Air Heater Pressure Drop



Unit 2 Extended Results

Paradise Unit 2 Air Heater Pressure Drop



Unit Performance Impacts

- Since January, 2011, over **570,000 MWh** have been lost as a result of air heater fouling from both units.
- Since hot side injection has been started, **0 MWh** have been lost as a result of air heater fouling.
- Contributing Factors:
 - Air Heater maintenance
 - Combustion Tuning
 - SCR catalyst replacement/ Tuning

Air Heater Exit Gas Temperatures

Paradise Unit 1 Average AH Exit Gas Temperature



Benefits

- Benefits of lowering the acid dew point are:
 - Slowing of APH corrosion mechanism
 - Increased chance of minimizing APH fouling by slowing the development of Ammonia-Bisulfate (ABS) driven fouling
 - SO_3 emissions at stack will continue to be mitigated


Paradise Unit 3

- Temporary hot-side injection system has been installed
- Split injection system as a result of downstream precipitators
- Initial testing will begin when unit returns to service
- Risks:
 - Fly ash resistivity
 - Hydroveyor pluggage

Cumberland

- Unit 2 hot side injection started in September of 2012.
- Air heater dP has increased at a lower rate compared to Unit 1 with downstream injection.
- Equipment on site to set up hot side injection on Unit 1.
- Opportunities for improvement:
 - Modify injection rate to maximize APH benefit while minimizing PPTR performance impacts.
 - Potential heat rate improvement by lowering APH exit gas temperature.
 - Injection logic changes to alleviate “morning sickness” effect.


Other Programs in 2013



Trial: Use of Hydrated Lime Pre-APH

- Large plant (>400 MW)
 - High Sulfur Coal, SCR, Cold side ESP, Wet FGD
- Post-APH injection of hydrated lime
 - APH Dp increase from Day 1
 - About 2-3 months before cleaning required
- Hydrated lime injection pre-APH
 - APH Dp steady
 - APH clean “outage to outage”

Hydrated Lime Pre-APH – Effects on APH dP




Trial: Pre-APH Comparison with FGT and HR Hydrate

- Large plant (>400 MW)
 - High Sulfur Coal, SCR, Cold side ESP, Wet FGD
- Injection Pre-APH, with SO₃ measurement at APH inlet using a Breen probe.
- Two hydrated limes evaluated at three feed rates each
 - FGT hydrate ('typical' DSI-grade hydrate)
 - High Reactivity hydrate (next generation hydrate)
- Averaged results at varying feed rates and unit loads

SO₃ Reduction at APH Inlet

SO₃ ppm at APH inlet Hydrate Injected at SCR Outlet



Other Discussion Items

- Pre-APH hydrate injection benefits units using DSI for mercury control
- Flue gas coverage is another key to good removal rates
- SO₃ levels can vary due to fuel, boiler, and SCR ops throughout the day
 - Reaction byproduct/intermediates have not proven to be an issue with hydrated lime

Summary

- Use of hydrated lime for SO_3 control prior to the APH is a rapidly growing practice for Utility boilers
- The advantages of hot side SO_3 control go beyond regulatory-mandated mitigation
- Pre-APH injection of hydrated lime offers significant cost saving potential to Utilities
- Use of a high quality, rapid reacting hydrated lime should be targeted for this process requiring in-flight capture of SO_3

Questions

Curt Biehn
Manager, Marketing and Technical Services
crbiehn@mississippilime.com
314.543.6309

Adam Harris
TVA – Systems Engineer
alharris0@tva.gov
423.751.6720



Discovering what's possible with calcium[™]