

REINHOLD ENVIRONMENTAL Ltd.



# **2017 NO<sub>x</sub>-Combustion-CCR Round Table Presentation**

February 27 & 28, 2017, in Cleveland, OH / Hosted by FirstEnergy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.



# CCR Groundwater Program Management & Risk Mitigation Strategies

Jason Eichenberger, PE  
Burns & McDonnell

Katie Bland, PE  
Burns & McDonnell

February 27<sup>th</sup>, 2017

# Introduction



**Jason Eichenberger, PE**

Associate Civil Engineer

CCR Business Unit Manager

[jeichenberger@burnsmcd.com](mailto:jeichenberger@burnsmcd.com)

816-822-3997



**Katie Bland, PE**

Process Section Manager

CCR Groundwater Specialist

[kbland@burnsmcd.com](mailto:kbland@burnsmcd.com)

816-823-7042

# Agenda



CCR Rule Overview: Groundwater Requirements



Timeline for Action



Case Studies



Conclusions




# CCR Overview: Groundwater

# Rule Requirements



## DESIGNING YOUR NETWORK


- ▶ Minimum of one upgradient and three downgradient wells
  - Typically more wells are recommended to accurately characterize site
- ▶ Downgradient wells at the waste boundary
- ▶ Monitoring of uppermost aquifer
- ▶ Multiunit networks are allowable



# CCR Compliance Schedule for Groundwater



- ▶ First report by January 31, 2018
- ▶ Rule provides detailed path for detection monitoring, assessment monitoring, and corrective action planning
- ▶ **Corrective action may begin as soon as first quarter of 2019**
  - Corrective Action strategy must go through public vetting process
  - Also requires risk assessment



# CCR Compliance Schedule for Groundwater



- ▶ Initiation of **Corrective Action Assessment** required within 90 days of Statistically Significant Increase (SSI); must be complete within 90 days of initiation
- ▶ 60-day extension is an option
- ▶ Requires PE certification of accuracy
- ▶ CA demonstration must be included in Annual Groundwater Monitoring Report (public posting via internet)
- ▶ **CA considered complete following 3 consecutive years of compliance with groundwater protection standard**

# Planning Ahead



## HOW LIKELY ARE GROUNDWATER IMPACTS?

- ▶ Review of EPA Findings:
  - 16 of 17 proven damage cases involved unlined facilities
  - 63% of operating landfills & impoundments are unlined
  - Data shows unlined impoundments typically operate up to 20 years before they begin to leak
  - Most currently operating impoundments are 20-40 years old



# Recent Developments



- ▶ Pending: June 14, 2016 Court approval of remand and remand/vacate motion
  - Add Boron to Appendix IV? – Remand Rule in 2019 TBD
  - Remove exemptions for Inactive CCR Surface Impoundments
    - ▶ Federal Register notice on August 5, 2016
    - ▶ Same requirements as for active CCR Surface Impoundments
    - ▶ Different Compliance Dates
      - April 17, 2019 Groundwater Monitoring System Requirements
      - August 1, 2019 Initial Groundwater Monitoring and Corrective Action Report

# Recent Developments




- ▶ “Water Infrastructure Improvements for the Nation Act” or the “WIIN Act” (Public Law No. 114–322)
- ▶ 42 USC § 6945 Upgrading of open dumps
  - (d) State programs for control of coal combustion residuals
    - ▶ 40 CFR § 257 or State permit program
    - ▶ 180 days for USEPA to approve State permit program
    - ▶ **“at least as protective as”**
    - ▶ technical standards that differ from the criteria under part 257 based on site-specific conditions are allowed if...
    - ▶ **IF** congress appropriates funds, USEPA shall implement permit program in a nonparticipating States
    - ▶ USEPA shall implement permit program for Native American Tribal Land.



# CCR Groundwater Management: Timeline


# Groundwater Management Timeline



# Background Monitoring



- ▶ Established With 8 Independent Baseline Samples
- ▶ Use Appropriate Data
  - ▶ Current Conditions
  - ▶ Upgradient vs. Downgradient
  - ▶ Consistent Sampling Techniques & Analytical Methods
  - ▶ Review for Trends, Outliers, Seasonality, and Spatial Variability



# Background Data



Represents Historical Conditions Unaffected by Site Activities

- ▶ Update Background Every 2 years
  - Higher “Statistical Power”
  - Increased Ability To Detect Changes In Concentration And/Or Releases



# Background Monitoring




## RISK FACTORS

- ▶ Field Work – collection of data/samples
- ▶ Sample Handling, Packaging, Shipping
- ▶ Laboratory
- ▶ Data Review and Management
- ▶ Statistical Analysis
- ▶ Reporting

## MITIGATE RISK

- ▶ Personnel Trained, Understand, and Follow Sampling & Analysis Plan
- ▶ Use Properly Working Field/Lab Equipment and Instruments
- ▶ Field/Lab Documentation and QA/QC
- ▶ Data Validation and Statistical Software/Method
- ▶ Groundwater Monitoring System Properly Designed, Constructed, and Developed




**Groundwater Data Accessible to Public - quality and defensible data**

# First Annual Report



## Site Characterization

- ▶ Robust statistical analysis
- ▶ Conceptual Site Model (CSM)



# Statistical Analysis



## METHODS

- ▶ Time Series
- ▶ Trend Tests (Sen's Slope/Mann Kendall)
- ▶ Outlier Tests
- ▶ T-Test (Mann-Whitney)
- ▶ Box & Whisker Plots
- ▶ Prediction Interval (background)
- ▶ Confidence Interval (GWPS)

## SELECTION

- ▶ Groundwater Results and Distribution of Data (normality and %NDs)
- ▶ Site Hydrogeological Conditions
  - Groundwater Flow
  - Spatial Variability




# Conceptual Site Model



## WHAT IS A CONCEPTUAL SITE MODEL?

- ▶ A 'living representation' of a site.
- ▶ Supports effective evaluation of site conditions and compliance strategies
- ▶ May consist of:
  - Maps and cross-sections
  - Risk exposure/pathway diagrams
  - Computer models





# Conceptual Site Model



## WHY IS A CSM IMPORTANT?


- ▶ Defines the problem
- ▶ Critical to the assessment/selection and design of cost-effective Corrective Measures
- ▶ Simulate “what if” scenarios
- ▶ Aids communication among team members, decision makers, stakeholders and field personnel.



# Conceptual Site Model



# Conceptual Site Model



# Conceptual Site Model



## WHAT DOES A GOOD CSM LOOK LIKE?

- ▶ Represents accurate interpretation of site data
- ▶ Confirmed or modified based on new data
- ▶ Holistic


## WHAT DOES A GOOD CSM DO?

- ▶ Defines the problem / risk
- ▶ Basis for confident, cost-effective decisions
- ▶ Basis for communication among team members, decision makers, and stakeholders

# Compliance Monitoring




- ▶ Detection Monitoring
- ▶ Assessment Monitoring
- ▶ Prepare for Corrective Action Assessment



# Compliance Monitoring



## ▶ Implement Detection vs. Assessment Monitoring?



## ▶ Dependent upon:

- Groundwater Data
  - ▶ Background and Compliance
- Statistical Analysis
  - ▶ SSI Verification Resampling
  - ▶ Alternate Source Demonstration

# Compliance Monitoring



## DETECTION MONITORING

- ▶ Sampling shall be done semiannually; unless there is inadequate groundwater flow, in which case sampling is done annually
- ▶ Purpose is to identify potential groundwater impacts with selected indicator parameters
- ▶ Establish assessment monitoring program within 90 days of an SSI found during detection monitoring

| <b>APPENDIX III<br/>CONSTITUENTS</b> |
|--------------------------------------|
| Boron                                |
| Calcium                              |
| Chloride                             |
| Fluoride                             |
| pH                                   |
| Sulfate                              |
| Total Dissolved Solids (TDS)         |

# Compliance Monitoring




## ASSESSMENT MONITORING

- ▶ Sample for Appendix IV constituents 90 days after triggering assessment monitoring, and annually thereafter
- ▶ Resample 90 days after obtaining results
- ▶ Establish groundwater protection standards during assessment monitoring for any constituents found to be SSIs
- ▶ If all constituents are at or below background for 2 consecutive events then return to detection monitoring
- ▶ Otherwise, move towards Corrective Action

| APPENDIX IV CONSTITUENTS  |            |
|---------------------------|------------|
| Antimony                  | Fluoride   |
| Arsenic                   | Lead       |
| Barium                    | Lithium    |
| Beryllium                 | Mercury    |
| Cadmium                   | Molybdenum |
| Chromium                  | Selenium   |
| Cobalt                    | Thallium   |
| Radium 226 & 228 Combined |            |
| Boron?                    |            |

# Compliance Monitoring




# Groundwater Corrective Measures Study



Preliminary assessment of site conditions, potential impacts, risk, and cost

- ▶ Conducted **prior to** *Assessment of Corrective Measures* mandated in 40 CFR § 257.96



# Groundwater Corrective Measures Study




- ▶ Reduced Uncertainty
  - Advanced Knowledge of Risk and Cost Drivers
- ▶ Early Identification & Screening of Compliance Strategies
- ▶ Identification of Cost-Saving Approaches
  - Alternative Source Evaluation
  - Monitored Natural Attenuation
- ▶ Integration with other CCR/ELG Compliance Strategies
- ▶ Reduced Schedule Pressure
- ▶ Improved Decision Making

# Groundwater Corrective Measures Study



|             | Alternative 1          | Alternative 2                                              | Alternative 3            | Alternative 4                           |
|-------------|------------------------|------------------------------------------------------------|--------------------------|-----------------------------------------|
| Description | No Corrective Measures | Monitored Natural Attenuation and Supporting Investigation | Small Scale Pump & Treat | Hydraulic Containment with Pump & Treat |
| 30 Year NPV | \$1,300,000            | \$2,800,000                                                | \$7,700,000              | \$25,800,000                            |

# Corrective Action Assessment



# Assessment of Corrective Measures



## Rule Requirements

### ▶ Public Notification

- Notification of GPS Exceedance
- Notification of Impacted Property Owners

### ▶ Release Characterization

- Must install and sample at least one additional monitoring well (per Rule)

### ▶ If alternative source or invalid exceedance cannot be demonstrated, begin Assessment of Corrective Measures

- 90 days to complete
- 60-day extension possible (Requires PE certification)
- Public meeting 30 days before selecting remedy
- 90 days after to selection to begin corrective action

# Assessment of Corrective Measures



## ▶ (a) Timing

- (a) ...as soon as feasible...

## ▶ (b) Requirements

- Be protective of human health and the environment
- Attain the groundwater protection standard
- Control the source(s) of Appendix IV constituents
- Remove contaminated material
- Comply with all applicable RCRA requirements


## ▶ (c) Evaluation factors

- ...magnitude of reduction of existing risks...
- ...magnitude of residual risk...
- ...risk due to implementation...
- ...potential for exposure...to remaining waste...


## ▶ (d) Schedule factors

- Nature and extent
- Potential risk
- Resource value of the aquifer


# Assessment of Corrective Measures



# Assessment of Corrective Measures



# Implement Corrective Action



# Corrective Action Timeline



## Groundwater Monitoring and Closure

- ▶ Consider Corrective Action costs/operation as part of your closure determination
- ▶ Monitoring well network design
- ▶ Statistical analysis
- ▶ Data validation

## Corrective Action


- ▶ #1 Objective – minimize or eliminate remediation
- ▶ Corrective Action Studies
- ▶ Risk Assessments
- ▶ Cost Modeling




# Corrective Action Compliance Strategies



- ▶ Monitored natural attenuation
- ▶ Institutional controls
- ▶ Hydraulic capture/containment
- ▶ In-situ treatment
- ▶ Ex-situ treatment
- ▶ Excavation/disposal
- ▶ Capping
- ▶ Combined remedies
- ▶ Solidification/Stabilization
- ▶ Phytoremediation
- ▶ Passive/reactive treatment barriers



# Implement Corrective Action – Inactives





# Case Studies


# Case Study 1: Impoundments in Series




- ▶ One impoundment is classified as active
- ▶ Two impoundments are classified as inactive and have begun the process for closure
- ▶ ELG compliance date is November 1, 2018




# Case Study 1: Impoundments in Series




# Case Study 2: Water Balance Management




# Alluvial Aquifer



# Treated Groundwater – Capital Cost



# Treated Groundwater – O&M Cost



# Groundwater Management: Holistic Strategies



## A Complex Problem Requires Planning


- ▶ Impoundment Closure Methods
  - Clean Closure vs. Cap In Place
- ▶ Corrective Action Strategies
  - Water treatment capacity
  - Plant water balance
  - Capital vs O&M
  - Risk Profile
- ▶ Permitting
  - Discharge options will be state specific
  - NPDES permit modifications?
  - Temporary discharges?



# Case Study 3: New Process Water Ponds?



- ▶ 2 Units at 250 MW – Midwest Location
- ▶ Project began in 2016
- ▶ Current ash pond receives flow from:
  - Coal Runoff Pond
  - Landfill Runoff Ponds
  - Rainfall runoff
  - Various process streams
    - ▶ Bottom ash sluice, pyrites, and economizer ash
    - ▶ Boiler area sumps
    - ▶ RO Reject
  - Outage flows:
    - ▶ Metal cleaning wastewater



# Pond Sizing Considerations



- ▶ TSS– Coal Pile Runoff
- ▶ Water Quality – Past Sampling Data
- ▶ Residence time – Target ELG Limit of 30 ppm TSS
- ▶ Footprint available – 26 acres
- ▶ Rainfall – Plant Runoff

| Stream Name      | S.G. | Daily    | TSS    | Volumetric Flow |         |
|------------------|------|----------|--------|-----------------|---------|
|                  |      | Capacity | (mg/L) | (GPM)           | (L/min) |
|                  |      | %        |        |                 | Avg     |
| Process Drains   | 2    | 100%     | 150    | 322             | 1,220   |
| Stormwater       | 2    | 5%       | 136    | 16,112          | 3,050   |
| Coal Pile Runoff | 1.4  | 5%       | 240    | 3,444           | 652     |

|                                      |      |
|--------------------------------------|------|
| 25-Year Storm Rainfall (in):         | 5.5  |
| Average Annual Rainfall (in):        | 46   |
| Equivalent Number of 25-Year Storms: | 8.36 |

# Process Streams



| Stream Description           | Average Flow, GPM | Adjusted Flow, GPM |
|------------------------------|-------------------|--------------------|
| Misc. Drains                 | 200               | 200                |
| Metal Cleaning Wastes        | 15                | 15                 |
| Bottom Ash Sluice System     | 4,500             | -                  |
| Bottom Ash Hopper Seal Water | 1,700             | -                  |
| Unit 1 Boiler Sump           | 2                 | 2                  |
| Unit 2 Boiler Sump           | 2                 | 2                  |
| Clarifiers A+B               | 104               | 104                |
| Total                        | 6,522             | 322                |

# Process Streams



| Stream Description           | Average Flow, GPM | Adjusted Flow, GPM |
|------------------------------|-------------------|--------------------|
| Misc. Drains                 | 200               | 200                |
| Metal Cleaning Wastes        | 15                | 15                 |
| Bottom Ash Sluice System     | 4,500             | -                  |
| Bottom Ash Hopper Seal Water | 1,700             | -                  |
| Unit 1 Boiler Sump           | 2                 | 2                  |
| Unit 2 Boiler Sump           | 2                 | 2                  |
| Clarifiers A+B               | 104               | 104                |
| Total                        | 6,522             | 322                |



## ► TSS Loading– Settling in Pond

- Coal Pile Runoff is design

| Stream Type      | Average TSS, ppm | Max TSS, ppm |
|------------------|------------------|--------------|
| Coal Pile Runoff | 60               | 240          |
| Storm Water      | 75               | 140          |
| WWT Effluent     | 5                | 5            |
| CTBD             | 50               | 50           |

## ► Rainfall

- 25 Year, 24-Hour Storm Event

| Runoff Streams    | Flow, GPM |
|-------------------|-----------|
| Coal Pile Runoff  | 3,444     |
| Plant Area Runoff | 2,462     |
| Runoff Pond A     | 884       |
| Runoff Pond B     | 3,726     |
| Runoff Pond C     | 6,348     |
| Rainfall          | 2,124     |

|                           | Coal Pile<br>Runoff Pond | Plant Island<br>area runoff | Misc.<br>Drains | Runoff<br>Pond A | Runoff<br>Pond B | Runoff<br>Pond C | Combined<br>Flow to Ash<br>Pond | ELG<br>Limit | Current<br>NPDES<br>Limits |
|---------------------------|--------------------------|-----------------------------|-----------------|------------------|------------------|------------------|---------------------------------|--------------|----------------------------|
|                           | 3444                     | 2462                        | 200             | 884              | 3726             | 6348             | 19171                           |              |                            |
| Water Analysis            |                          |                             |                 |                  |                  |                  |                                 |              |                            |
| pH                        | 4.2                      | 8.1                         | 6.50            | 9.10             | 7.7              | 7.7              | 7.32                            |              | 6-9                        |
| Acidity                   | 3298.85                  | --                          | --              | --               | --               | --               | 592.63                          |              |                            |
| Arsenic                   | .0019                    | .0014                       | 0.01            | 0.138            | .0499            | .0499            | 0.06                            | 0.01         |                            |
| Chromium                  | .0017                    | .0007                       | 0.00            | ND               | .0017            | .0017            | 0.02                            | 0.20         | 0.2 mg/L                   |
| Copper                    | .021                     | .006                        | 0.01            | ND               | ND               | ND               | 0.03                            | 1.00         | 1.0 mg/L                   |
| Iron                      | 67.3                     | .545                        | 14.06           | 0.035            | .727             | .727             | 16.13                           |              | 1.0 mg/L                   |
| Mercury                   | ND                       | ND                          | 0.00            | ND               | .0002            | .0002            | 0.00                            | 0.001        |                            |
| Selenium                  | .020                     | ND                          | 0.01            | 0.019            | .004             | .004             | 0.01                            | 0.02         |                            |
| Zinc                      | .49                      | ND                          | 0.03            | 0.02             | .02              | .02              | 0.10                            | 1.00         | 1.0 mg/L                   |
| Oil and Grease            | ND                       | ND                          | 5.07            | ND               | ND               | ND               | 0.52                            | 20.00        | 17 mg/L                    |
| Total Dissolved<br>Solids | 3730                     | 244                         | 101.75          | 2560             | 4050             | 4050             | 3,128.48                        | 50 (BAT)     |                            |
| Total Suspended<br>Solids | 28.8                     | 43                          | 113.00          | 6.6              | 31.2             | 31.2             | 168.00                          | 30           | 30 mg/L                    |
| Chloride                  | 576                      | 12.6                        | 9.46            | 187              | 975              | 975              | 646.89                          |              | 1200<br>mg/L               |
| Nitrate as N              | 1                        | .8                          | --              | ND               | 1.4              | 1.4              | 1.03                            | 17.00        |                            |
| Nitrite as N              | ND                       | ND                          | --              | ND               | ND               | ND               | --                              | 17           |                            |

|                           | Coal Pile<br>Runoff Pond | Plant Island<br>area runoff | Misc.<br>Drains | Runoff<br>Pond A | Runoff<br>Pond B | Runoff<br>Pond C | Combined<br>Flow to Ash<br>Pond | ELG<br>Limit | Current<br>NPDES<br>Limits |
|---------------------------|--------------------------|-----------------------------|-----------------|------------------|------------------|------------------|---------------------------------|--------------|----------------------------|
|                           | 3444                     | 2462                        | 200             | 884              | 3726             | 6348             | 19171                           |              |                            |
| Water Analysis            |                          |                             |                 |                  |                  |                  |                                 |              |                            |
| pH                        | 4.2                      | 8.1                         | 6.50            | 9.10             | 7.7              | 7.7              | 7.32                            |              | 6-9                        |
| Acidity                   | 3298.85                  | --                          | --              | --               | --               | --               | 592.63                          |              |                            |
| Arsenic                   | .0019                    | .0014                       | 0.01            | 0.138            | .0499            | .0499            | 0.06                            | 0.01         |                            |
| Chromium                  | .0017                    | .0007                       | 0.00            | ND               | .0017            | .0017            | 0.02                            | 0.20         | 0.2 mg/L                   |
| Copper                    | .021                     | .006                        | 0.01            | ND               | ND               | ND               | 0.03                            | 1.00         | 1.0 mg/L                   |
| Iron                      | 67.3                     | .545                        | 14.06           | 0.035            | .727             | .727             | 16.13                           |              | 1.0 mg/L                   |
| Mercury                   | ND                       | ND                          | 0.00            | ND               | .0002            | .0002            | 0.00                            | 0.001        |                            |
| Selenium                  | .020                     | ND                          | 0.01            | 0.019            | .004             | .004             | 0.01                            | 0.02         |                            |
| Zinc                      | .49                      | ND                          | 0.03            | 0.02             | .02              | .02              | 0.10                            | 1.00         | 1.0 mg/L                   |
| Oil and Grease            | ND                       | ND                          | 5.07            | ND               | ND               | ND               | 0.52                            | 20.00        | 17 mg/L                    |
| Total Dissolved<br>Solids | 3730                     | 244                         | 101.75          | 2560             | 4050             | 4050             | 3,128.48                        | 50 (BAT)     |                            |
| Total Suspended<br>Solids | 28.8                     | 43                          | 113.00          | 6.6              | 31.2             | 31.2             | 168.00                          | 30           | 30 mg/L                    |
|                           |                          |                             |                 |                  |                  |                  | Settling In Pond                |              |                            |
| Chloride                  | 576                      | 12.6                        | 9.46            | 187              | 975              | 975              | 646.89                          |              | 1200<br>mg/L               |
| Nitrate as N              | 1                        | .8                          | --              | ND               | 1.4              | 1.4              | 1.03                            | 17.00        |                            |
| Nitrite as N              | ND                       | ND                          | --              | ND               | ND               | ND               | --                              | 17           |                            |


|                           | Coal Pile<br>Runoff Pond | Plant Island<br>area runoff | Misc.<br>Drains | Runoff<br>Pond A | Runoff<br>Pond B | Runoff<br>Pond C | Com<br>Flo       | Additional<br>Chemical Feed<br>Needed | Current<br>PDES<br>Limits |
|---------------------------|--------------------------|-----------------------------|-----------------|------------------|------------------|------------------|------------------|---------------------------------------|---------------------------|
|                           | 3444                     | 2462                        | 200             | 884              | 3726             | 6348             |                  | 171                                   |                           |
| Water Analysis            |                          |                             |                 |                  |                  |                  |                  |                                       |                           |
| pH                        | 4.2                      | 8.1                         | 6.50            | 9.10             | 7.7              | 7.7              |                  | 32                                    | 9                         |
| Acidity                   | 3298.85                  | --                          | --              | --               | --               | --               |                  | 2.63                                  |                           |
| Arsenic                   | .0019                    | .0014                       | 0.01            | 0.138            | .0499            | .0499            |                  | 0.06                                  | 0.01                      |
| Chromium                  | .0017                    | .0007                       | 0.00            | ND               | .0017            | .0017            |                  | 0.02                                  | 0.20                      |
| Copper                    | .021                     | .006                        | 0.01            | ND               | ND               | ND               |                  | 0.03                                  | 1.00                      |
| Iron                      | 67.3                     | .545                        | 14.06           | 0.035            | .727             | .727             |                  | 16.13                                 | 1.0 mg/L                  |
| Mercury                   | ND                       | ND                          | 0.00            | ND               | .0002            | .0002            |                  | 0.00                                  | 0.001                     |
| Selenium                  | .020                     | ND                          | 0.01            | 0.019            | .004             | .004             |                  | 0.01                                  | 0.02                      |
| Zinc                      | .49                      | ND                          | 0.03            | 0.02             | .02              | .02              |                  | 0.10                                  | 1.00                      |
| Oil and Grease            | ND                       | ND                          | 5.07            | ND               | ND               | ND               |                  | 0.52                                  | 20.00                     |
| Total Dissolved<br>Solids | 3730                     | 244                         | 101.75          | 2560             | 4050             | 4050             |                  | 3,128.48                              | 50 (BAT)                  |
| Total Suspended<br>Solids | 28.8                     | 43                          | 113.00          | 6.6              | 31.2             | 31.2             |                  | 168.00                                | 30                        |
|                           |                          |                             |                 |                  |                  |                  | Settling In Pond |                                       |                           |
| Chloride                  | 576                      | 12.6                        | 9.46            | 187              | 975              | 975              |                  | 646.89                                | 1200<br>mg/L              |
| Nitrate as N              | 1                        | .8                          | --              | ND               | 1.4              | 1.4              |                  | 1.03                                  | 17.00                     |
| Nitrite as N              | ND                       | ND                          | --              | ND               | ND               | ND               |                  | --                                    | 17                        |

# Water Mass Balance Pond - Chemical Feed




- ▶ Minimal Sampling Data Available
  - Future sampling plan developed to gather more complete data
- ▶ Chemical Feed System to account for Iron and Arsenic
  - Caustic – to regulate pH
  - Polymer – to promote metals settling
  - Acid – to regulate pH in event of algae blooms

# Effect of Rainfall



# Effect of Rainfall



# Final Design – New Water Mass Balance Pond



- ▶ Required Acreage – 10 acres
- ▶ Available Acreage –
  - 20 acres (partial closure)
  - 26 acres with full removal
- ▶ Time to accumulate 1 ft of sludge – 4 years



# Costs For Closure of Ash Pond



- ▶ Mobilization/Demobilization
- ▶ Dewatering
- ▶ General Site Prep
- ▶ Pond Solids Cut to Fill
- ▶ Pond Solids Excavate to Landfill
- ▶ Pipe Demolition
- ▶ Subgrade Compaction
- ▶ Composite Liner
- ▶ Protective Cover
- ▶ Slope Protection
- ▶ QA/QC
- ▶ Water Treatment Rental

Total Costs (Direct, Indirect, Contingency) for Closure by Removal of CCR Material - \$40 million



# Conclusions


# Conclusions



## Start Planning Now

- ▶ Start evaluating groundwater data to determine whether or not groundwater impacts are probable
- ▶ Consider a Conceptual Site Model to get a detailed understanding of subsurface conditions on your site
- ▶ Corrective Action Assessment – do this now and get an appropriate range of costs in the budget
- ▶ Evaluate your current plant water balance; it is up to date? Need seasonal flow and constituent data
- ▶ Begin evaluation of an added water source; could this replace or decrease your current fresh water use?





CREATE AMAZING.

Jason Eichenberger, PE - [jeichenberger@burnsmcd.com](mailto:jeichenberger@burnsmcd.com) - 816/822/3997

Katie Bland, PE - [kbland@burnsmcd.com](mailto:kbland@burnsmcd.com) - 816/823/7042

# References



USEPA, 2001, *Cost Analyses for Selected Groundwater Cleanup Projects: Pump and Treat Systems and Permeable Reactive Barriers.*

USEPA, 2014, *Regulatory Impact Analysis; EPA's 2015 RCRA Final Rule Regulating Coal Combustion Residual (CCR) Landfills and Surface Impoundments at Coal-Fired Electric Utility Power Plants.*

USEPA, 2015, *Hazardous and Solid Waste Management System; Disposal of Coal Combustion Residuals from Electric Utilities; Final Rule*, 40 CFR Parts 257 and 261, Federal Register, Vol. 80, No. 74, April 17, 2015.

USEPA, 2015, *Effluent Limitations Guidelines and Standards for the Steam Electric Power Generating Point Source Category; Final Rule*, 40 CFR Part 423, Federal Registers, Vol. 80, No. 212, November 3, 2015.