

REINHOLD ENVIRONMENTAL Ltd.



2017 NO_x-Combustion-CCR Round Table Presentation

February 27 & 28, 2017, in Cleveland, OH / Hosted by FirstEnergy

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

Modifications to Existing Overfire Air Systems for Improved NO_x Control

Blake Stapper, Pat Crotty, Guisu Liu

Presented at the 2017 NO_x-Combustion-CCR Round Table & Expo

February 28, 2017

AECOM

Outline

- Approach to Cost-effective Compliance Solutions
- ROFA System Description
- Application of CFD Engineering
- Results
 - 380 MW unit
 - 500 MW unit
- Summary



Layered Approach for Emissions Compliance

Primary Measures

- Combustion Tuning
- Low-NO_x Burners
- Over-fire Air
- Boiler Optimizer


Critical Step: Minimize boiler outlet NO_x emissions



Secondary Measures

- SNCR
- SBS
- LoTOx


Trim to compliance limits



Flexible, cost-effective alternatives to SCR

ROFA® (Rotating Opposed-fire Air)


- Method of staging combustion using boosted secondary air to create turbulence in the upper furnace for improved flue gas mixing resulting in optimum NO_x reduction, CO and LOI
- System designed based on actual furnace readings, flue gas traverses and vast experience utilizing CFD engineering
- Implemented in conjunction with burner/secondary air modifications



System Design

Major equipment list

- Boosted fan
- Ductwork / expansion joint
- ROFA boxes
- Modulated dampers
- Secondary air nozzles
- Electrical and I&C



Air Duct

ROFA Box


ROFA Nozzle

Air Damper




CFD Engineering to Improve Combustion Quality

- CFD-assisted placement of injection boxes utilizing actual furnace data
- Multiple air nozzles to ensure maximum flue gas coverage
- Better mixing due to energy imparted to flue gas
- Increased residence time for more complete combustion



Streamlines



Air Jets (Plan View)

Improved Combustion Allows for Deeper Staging

- Better mixing of air and fuel in upper furnace reduces CO and LOI
- Allows for operation with decreased excess oxygen, resulting in lower heat rate
- Sustained NO_x reduction performance at reduced load
- Modifications to secondary air nozzles
 - Manage windbox/furnace ΔP
 - Maintain oxygen concentration along walls
- No evidence of increased water wall tube wastage




380MW Unit

- Tangentially-fired tower boiler
- Bituminous coal
- CCOFA and SOFA previously installed
 - Adjustable yaw
 - Fixed tilt
 - Design for 20% TAF for overfire air system
 - Reduced to ~13% TAF to avoid tube wastage
- Baseline NO_x: 0.32-0.36 lb/MMBtu




380MW Unit - Modifications


- Retained CCOFA, but modified nozzles
 - Smaller cross-section to increase velocity
 - Allow for horizontal directional adjustment
- Removed SOFA
- Modifications to secondary air nozzles
- Implemented two levels of ROFA nozzles
 - Six ports at SOFA elevation; used two of the existing SOFA penetrations on front and rear walls
 - Six additional ports, three each in side walls, located 16 feet above SOFA elevation
- ROFA TAF = 30%



380 MW Unit - Schematic of ROFA port locations



Front Wall
Lower Elevation



Front Wall
Upper Elevation

380 MW Unit - Installation




ROFA Ducting



Lower Level Nozzles in Furnace


380MW Unit - Results

- 44% NO_x reduction (from ~0.32 lb/MMBtu)
 - 0.18 lb/MMBtu at full load
 - 0.14 lb/MMBtu at 210 MW
- CO < 50 ppm
- LOI: 3.5%
- Excess oxygen decreased from 3.8% to 2.7%
- 0.7% decrease in net unit heat rate
- Demonstrated ability to handle significant fuel variability




500MW Unit

- Tangentially-fired twin-furnace
- Variety of international coals
- CCOFA and SOFA previously installed
 - Two CCOFA nozzles at each corner, injecting 4% of TAF
 - Two SOFA ports on front and rear wall of each furnace, injecting 8% of TAF
- Baseline NO_x : 0.33 lb/MMBtu at full load with both CCOFA and SOFA in service
- SOFA typically out of service to avoid high dust levels, resulting in high- NO_x operating mode
- Elevated baseline CO (700ppm) and LOI (14%)





500MW Unit - Modifications

- ROFA ports located at two levels
 - 4 ports each furnace, located 8 feet above SOFA elevation
 - 2 ports each furnace, located 16 feet above SOFA elevation
- Incorporated CCOFA and SOFA into overall NO_x control system
- Modifications to secondary air nozzles
- ROFA TAF = 25%




500MW Unit – Schematic of ROFA Port Locations



500MW Unit - Results

- 39% NO_x reduction (60% from “SOFA-off”)
- Performance test results at full load
 - NO_x: 0.20 lb/MMBtu
 - CO decreased to 150 ppm
 - LOI decreased to 8.2%
- Minimal change in boiler efficiency
- Demonstrated ability to handle significant fuel variability
- Utilized SNCR to achieve IED compliance



Summary

- ROFA system has been applied to boilers with existing CCOFA and SOFA
- Achieved ~40% additional NO_x reduction
- Effectively managed CO and LOI
- Maintained or increased boiler efficiency
- Reduction in NO_x formation enables implementation of secondary measures for regulatory compliance solution
- Helps create opportunity to avoid SCR

