

REINHOLD ENVIRONMENTAL Ltd.



**2019 REINHOLD Round Table
Presentation**

June 24 & 25, 2019, in Birmingham, Alabama / Hosted by Southern Company

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

ZLD Design and O&M Best Practices

*Presented by:
Michael Jaubert
Michael Pudvay*

ZLD Design and O&M Presentation Overview


- Experience Summary
 - *20 plus years operating: Pretreatment, precipitation softening, I/X, microfiltration, UF, MMF, high pH, RO, evaporators, crystallizers*
- Design Build Operate (DBO) and Engineer Procure Operate (EPO)
 - *Influent flow and loading variation*
 - *Treatment objectives and availability requirements*
 - *Where do you “draw the box?”*
 - *Tankage, redundancy and catch-up capacity*
 - *Critical spares*
- Operations lessons learned
 - *Process control - Sampling, analysis, field and on-line data all get married*
 - *Asset Management – are you managing the assets or vice versa?*
 - *Managing downtime and the “bad actors”*
- Recommendations
 - *Design*
 - *O&M*

Summary of Experience – Project overview

- HPD ZLD -- Harquahala and Red Hawk
- 11 years - Metals precipitation, filtration, crystallization with product recovery
- 7 years - Softening, MMF, RO, second stage softening, evaporation and crystallization
- 19 years - Softening, filtration, RO, recovery RO, crystallization
- 2 years – Selective Ion removal, multi-effect crystallization
- 30+ years total – 3 systems - high-recovery (high pH) RO systems including softening, filtration, I/X



DBO/EPO Facility Design Collaborative Approach



Collaboration during design and development includes:

Specifications, effluent quality and availability required

Influent variation, equalization and intermediate tankage

Catch-up capacity, Redundancy requirements and critical shelf spares

Customer Always Wins!

Design Considerations

- Influent flow review – how it varies both hydraulically and constituent variability
 - *Upstream tankage – allows accepting influent when production limited*
 - *Add mixing to provide loading equalization – will optimize chemical consumption and RO recovery*
 - *Ponds – good for size but need to manage biological activity*
- Effluent or product– if supplying critical process water evaluate effluent tank with similar approach
 - *12 hours of storage allows short outages without interrupting process*
- Summary
 - *When evaluating system availability to receive influent and provide product water “draw the box” to include influent and product tanks*
 - *Operate with influent tank low and product tank high*
 - *Include catch-up capacity in the design to allow re-establishing desired tank levels in a reasonable time*

ZLD System with 1-day storage tank - 98%



Thermal Design

- Including storage upstream of thermal allows “uncoupling of pretreatment/membrane from thermal
- Designing tank plus catch-up capacity for thermal provides lowest life-cycle cost
- Redundancy and Critical Spares
 - **Consider redundant:** level transmitters, pH meters, salt dewatering, preheaters, transfer pumps, metering pumps
 - **Consider complete rotating assemblies for:** Recirculation pumps, fans, compressors and centrifuges – include provisions for remove and replace
- Plan for periodic cleaning: chemically or mechanically based on chemistry and experience
 - *Include access and infrastructure to open heater and platform to hydroblast safely*
 - *Consider Clean-in-place for preheaters – full flowrate during cleaning is best*
 - *Boil-outs can be effective if buildup is water soluble – consider timing and frequency in availability calculations*
 - *Consider buildup on crystallizer walls – spray nozzles or periodic boil-outs*

Process Control – Critical!

- **Combine:** sampling, analysis, on-line and field readings in a single database to support calculations trending and key performance indicators (KPI) development
- On-line instruments are great – but must be calibrated and validated
- Sampling and analysis always required
- Hardness, alkalinity, silica, and pH are key in pretreatment




Process Control – Critical!

- RO normalization and stage dP provides early detection to problems
- Confirm all metering pumps, anti-scale etc are delivering with field checks
- Heat Transfer Coefficients and Boiling Point Rise for thermal – online
- Crystal inventory or Apparent Settled Volume and pH – sample it!



Process Control Example Membrane Performance Trending



Clean-in-place occurred on June 3rd based on 1st stage high dP

Process Control Example – Crystallizer Control

- Key aspects of crystallizer control:
 - *pH for corrosion control*
 - *ASV for tube fouling and recirc pump amps*
 - *CO3 for scaling*
 - *BPR for capacity*
 - *Fines control*
 - *Periodic mini-flushes, wall washes for growth control*

#	Parameter	Units	Average Over Date Range	Flag	Sample	08/10/14	08/11/14	08/12/14	08/13/14	08/14/14	08/15/14	08/16/14
2117	Crystallizer Recirculation Pump P-3063 A	AMPS			0							
2008	Crystallizer VB Pressure PIC 3061A	PSIG	0.55		27	0.40	0.55	0.60	0.53	0.53	0.60	0.63
2124	Crystallizer Vapor Body Temperature	DEG F	234.15		27	235.00	233.75	233.50	234.00	234.00	234.00	234.67
2119	Crystallizer Specific Gravity Vapor Body		1.28		27	1.28	1.28	1.29	1.29	1.28	1.28	1.28
2126	Crystallizer HTC	BTU/scft/F	923		27	911	877	820	886	989	1,017	1,007
2012	Crystallizer Boiling Point Rise BPR 3062	DEG F	22		27	22	21	22	22	22	22	22
2015	Crystallizer Fan IG V #1 HV 3065	%	33		27	35	33	32	32	32	32	32
2016	Crystallizer Fan Amps #1 II 3068	AMPS	66.26		27	69.25	66.50	66.50	65.50	65.25	65.00	66.00
2019	Crystallizer Fan IG V #2 HV 3071	%	30.63		27	33.00	30.75	30.00	30.50	30.00	30.00	30.00
2020	Crystallizer Fan Amps #2	AMPS	65.11		27	69.50	65.25	64.50	63.00	64.25	64.00	65.00

Asset Management – Keep It Simple

The purpose of the Asset Management program is to aid the project in managing the assets, including:

1	Document all maintenance performed on equipment (planned, unplanned, repeat, project, etc.) including technician notes, measurements, observations, actions, etc...
2	Document maintenance costs and man-hours required – supports repair/replace/upgrade evaluations
3	Schedule and track Preventative Maintenance and Predictive Maintenance activities (time directed, condition directed and failure-finding)
4	Support all internal, environmental, safety, warranty and Customer reporting requirements
5	Track critical spares inventory
6	“If it’s simple – they will use it”

Asset Management Report Example



Work Order Report

4/14/2016

WO Number	Work Type	PM Number	Equip Desc	Request	Comp Remark	Target Date	Comp Date
83750	CMP		U-2240 Soda Ash Silo	SODA ASH RUBBER BOOT FROM FEEDER LEAKING NEED TO REPLACE CURRENT BOOT WITH NEW RUBBER BOOT.	Shut silo down 2 hours and repaired feed tube.	2/26/2016	3/1/2016
83885	CMP		U-3081B CHRYSTALIZER CENTRIFUGE	Feed tube Flush is leaking distillate, it appears to have a cracked sight glass.	done during processing no downtime Replaced flow indicator.	2/29/2016	3/1/2016
83892	CMP		P-2223 B1 Silo 2 Lime feed pump A	Pump needs re-packed, almost out of adjustment. Only operational pump in Lime Silo B	EQUIPMENT IS SPARED SO NO DOWNTIME Added ring of packing and adjusted.	3/4/2016	3/1/2016
83728	PM	2125	A-2210; Polymer Mix Tank Agitator	Dry Polymer System Monthly Maintenance/Inspection	done during processing no downtime Inspected polymer system.	1/16/2016	3/1/2016
83729	PM	2129	F-3005 Automatic self Backwashing Strainer	F-3005; MONTHLY STRAINER INSPECTION/LUBRICATION	done during processing no downtime Strainer has been serviced. Hours 114.8	12/20/2015	3/1/2016
83730	PM	2144	P-2031A MMF FEED PUMP	P-2031A; MOTOR LUBE, MMF FEED PUMP	EQUIPMENT IS SPARED SO NO DOWNTIME Motor has been lubricated. Hours 23,380.3	1/29/2016	3/1/2016
83731	PM	2145	P-2031B FILTER FEED PUMP	P-2031B; MOTOR LUBE, MMF FEED PUMP	EQUIPMENT IS SPARED SO NO DOWNTIME Motor has been lubricated. Hours 9,526.3	1/29/2016	3/1/2016

Heads up on potential bad actors – We have seen them all

- Lime delivery
- Polymer dosing
- Biological fouling on membranes and cartridge filters
- RO recovery too optimistic for long-term reliability
- Post precipitation downstream of softening reactors
- Dewatering and solids logistics – don't skimp here
- Scale inhibitors interfering with desired precipitation
- Thermal startup and shutdown time is significant
- Preheater scaling and plugging

Heads up on potential bad actors – We have seen them all

- Slurry piping reliability
- Centrifuge reliability including washing provisions that do not compromise salt moisture
- Maintaining correct crystal inventory, pH and BPR in crystallizers and evaporators
- Hydroblasting timing and equipment requirements
- Process vapor quality and carry-over considerations for fans and compressors
- Vapors from thermal vents, centrifuge and tanks cause external corrosion and safety risk
- Startup resource requirements and ramp-up times

Recommendations

- Establish solid design basis – flow loading and variability – consider the future
- Draw the box around the entire system including tankage and confirm system meets production, availability and quality requirements
- Consider critical spares, catch-up capacity, maintenance and process interruptions, accessibility when calculating system availability and production potential



Recommendations

- Leverage actual long-term experience to mitigate process and O&M risk whenever possible – visit reference sites – minimize “World’s first of its kind” unit ops
- Expect and facilitate reasonable Performance Demonstration from EPC provider
- Use process control and asset management to be proactive rather than reactive. In ZLDs, often once ROs and heaters are limiting – it’s too late
- If in doubt – consider DBO/EPO – the customer always wins!



Thank You!



Questions?