

REINHOLD ENVIRONMENTAL Ltd.



**2015 APC Round Table  
& Expo Presentation**

July 13 & 14, 2015, in Atlanta, GA / Hosted by Southern Company

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.




# Evolution of the Hydrated Lime DSI System



Discovering what's possible with calcium

Curt Biehn, Chad Donner, and Cal Lockert  
Workshop 11 - APC Conference - Atlanta  
July 14, 2015




# Understand Capabilities of DSI System

## What are you playing: Defense or Offense?

- Hydrated lime
  - \$/ton vs. \$/ton of pollutant removed
- Feed system
  - Low cost system vs. cost effective system
- Mitigation plan
  - Understanding flue gas characteristics

# Hydrated Lime DSI System



- Flue injection performed at multiple ports in each injection location
- Sites can inject at one or multiple locations
- System OST and flue coverage are key

# Evolution of Hydrated Lime DSI

- First systems installed in 1990's
  - ‘Manual’ tests at TVA
  - Temporary then permanent
- Steep learning curve (2007-2010)
  - Plugging and scaling are prevalent
  - Problems with large, new systems
  - Trial systems also have issues
- Improved understanding of key factors (2009-2012)
  - DHUG
  - Keep hydrate in suspension
  - Control scale buildup
  - Better trial systems




# Evolution of Hydrated Lime DSI

- **Many sites are installing systems correctly at the start or have retrofitted improvements**
  - DHUG a big part of it
- Pockets of problems remain
- Many advances aimed at improved On Stream Time and higher performance


# Reactivity & Removal

- Thermodynamic
  - $\text{SO}_3 > \text{SO}_2 > \text{HF} > \text{HCl}$
- Kinetic
  - Maximize collisions
  - Hydrate  $D_{50} \sim 2\text{-}4 \mu\text{m}$
  - Gas particles  $\sim 0.0003 \mu\text{m}$

## Competing Reactions with $\text{Ca}(\text{OH})_2$




Benson, 2012 DHUG




# Bad Sorbent + Bad System



# Market Needs for Higher Performing Hydrate



# Full Scale Evaluation – SO<sub>3</sub> Removal - HR vs. FGT




**FGT hydrate gives good removal**


**HR Hydrate offers better utilization or high level removal capabilities**

# Utility MATS for HCl with Hydrated Lime

(smaller unit < 300 MW, IBC)




# Hydrated Lime DSI for SO<sub>2</sub> Control



# Pilot Plant SO<sub>2</sub> Reduction: HRH-64

- In-flight capture
- Poor conditions for SO<sub>2</sub> reduction with hydrate
  - Temp ~320 F
  - Low moisture
- New product significantly improved over HRH



## HRH-64: Industrial Boiler DSI

---

### HRH

- HCl reduction
  - 90-95%
- SO<sub>2</sub> reduction
  - 8-15%

### HRH-64

- HCl reduction
  - 97-99%
- SO<sub>2</sub> reduction
  - 20-44%

Inject post-Economizer

Stoichiometric ratio range of 1.5 – 3.0

# Chad's slides

---

# Cal's slides

---

# Questions



Cal Lockert  
clockert@breenes.com  
412-431-4499



Chad Donner  
chad.donner@duke-energy.com  
513-287-3127



Discovering what's possible with calcium™

Curt Biehn  
crbiehn@mississippilime.com  
314.543.6309