

REINHOLD ENVIRONMENTAL Ltd.



**2013 NO_x-Combustion Round Table
& Expo Presentations**

February 18 & 19, 2013, in Salt Lake City, UT / Hosted by PacifiCorp

All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.



DSI Experience Injecting Hydrated Lime Upstream of an Air Heater

Jim Dickerman – Lhoist North America



Reinhold NOx Combustion Mtg
February 19, 2013




Workshop Topics

- **WHO** – is injecting hydrated lime upstream of their air heater
- **WHAT** – is Dry Sorbent Injection (DSI)
- **WHY** – should this topic be of interest to you, and why are those that are doing it doing it
- **WHERE** – is upsteam hydrate injection being done
- **WHEN** – should you be considering this option





DSI Flow Diagram





DSI – Background

- Late 60's – TVA experimented with limestone boiler injection
- 1970's and 1980's – Nahcolite and trona injection
- 1984 – 1991 LIMB Project sponsored by EPA & DOE
 - ✓ Technology basically abandoned due to no commercial interest
- 2003 – The need for SO₃ control revived interest in duct injection
 - ✓ Early technology concerns/issues
 - Fouling of utility ducts/downstream equipment
 - Injection equipment issues
 - ✓ Technology concerns have basically been resolved and DSI is widely used commercially for SO₃ mitigation
- MATS has resulted in need for HCl and Hg control data
- CSAPR has renewed interest in SO₂ control
- European and Asian MSW experience has shown high removal levels for both HCl and SO₂




Factors Affecting DSI Effectiveness

Moisture Content




Surface Area and Pore Size



Temperature



Available Calcium



Available Sodium





SO₃ Removal – Sorbent Choice?

Trona

■ Use when:

- Need very high removals (> 90%)
- ESP can't handle hydrated lime without a particulate increase
- Ash sales not a concern
- Have high levels of SO₃
 - › Milled trona injection lowest injection rate/operating cost


Hydrated Lime

■ Use when:

- Need to preserve ash sales
- Relatively low SO₃ and, therefore, low injection rates
- Want to inject at FGD inlet and scrubber chemistry concerns
- Want to inject at AH inlet without sodium bisulfate formation risk



Courtesy of UCC





Reagents are NOT all the same

- Hydrate
 - ✓ Surface area
 - ✓ Porosity
- Trona
 - ✓ Unmilled
 - ✓ Milled





Physical Properties of Two Hydrates

- Chemically the hydrated limes are basically the same
- Their difference lies in their physical properties

Sorbacal

Standard Hydrate


SSA - $\sim 20 \text{ m}^2/\text{g}$

Porosity - $\sim .07 \text{ cm}^3/\text{g}$






SO₂ Removal @ Air Heater Inlet T





HCl Removal With ESP

ESP Operations @ 350°F




SO₃ Removal Injection Locations?



SCR Inlet

- Demonstrated successfully
- More sorbent needed (due to reaction w/ SO₂ for trona or CO₂ for hydrated lime)
- Long-term effects on catalyst unknown
- HCl co-benefit
- Hg affects unknown
- Remove SO₃ and metals before catalyst and AH
- May prevent ABS formation in AH
- Allow for back-end cooling
- Only available location for some units



FGD Inlet

- Injection rates somewhat limited – good location for lower sulfur coals
- Lose benefits of upstream SO₃ removal, but no risk of ESP effects
- Lose HCl/Hg co-benefits

SCR Outlet/Air Heater Inlet

- Demonstrated Successfully
- More sorbent needed
- HCl/Hg co-benefits may prevent ABS formation in AH
- Allow for Back-end cooling
- Only available location for some units

Air Heater Outlet

- Most common location
- Lowest sorbent use
- Most economical location if only need plume mitigation
- Sorbent may affect ESP, but low risk
- HCl/Hg co-benefits

Courtesy of UCC



WHY Have DSI Upstream of Your Air Heater?

- New REGIONAL HAZE Regulations can require SCR systems for NO_x control and this will increase SO₃ in the flue gas
- DSI is to remove SO₃
- Benefits of SO₃ removal
 - ✓ Improved air heater performance
 - ✓ Corrosion control
 - ✓ Enhanced mercury removal performance





Improved Air Heater Performance

- Both SCR and SNCR systems have some NH_3 slip
- SO_3 can react with NH_3 to form Ammonia bisulfate (ABS)
- ABS can attach to air heater surfaces, it will build up and increase the ΔP
- Removing SO_3 prevents ABS from forming, plus it allows better performance of SCR & SNCR by allowing larger amounts of NH_3 slip






Reduced Corrosion

- SO_3 can condense on downstream equipment and will increase corrosion
- DSI removes SO_3 and prevents corrosion in downstream equipment
- Reduced SO_3 also reduces the acid dew point which can allow the boiler to operate at a lower outlet T
 - ✓ Improves boiler heat rate
 - ✓ Reduces gas volume and ash resistivity for better ESP performance



Acid Dew Point as a Function of SO₃ Concentration





Impact of Decreased Air Heater Temperature

Rule of thumb – a 10°F temperature change at the air heater = 0.25% efficiency impact

- Calculation Basis
 - ✓ 500 MW boiler
 - ✓ 10,000 BTU/kw-hr heat rate
 - ✓ 8600 BTU/lb coal
 - ✓ 0.5% S
 - ✓ 100% capacity factor
 - ✓ Coal price = \$25/ton delivered
- A 10°F temperature reduction improves the heat rate to 9,975 BTU/kw-hr
- Base amount of coal –
 - ✓ 2,546,512 tons/yr
- Coal use at improved heat rate
 - ✓ 2,540,145 tons/yr
- Annual coal reduction
 - ✓ 6,367 tons
- **Annual savings = ~\$150,000**






Improved Mercury Removal Performance

- Data show that small amounts of SO_3 (3 – 5 ppm) greatly impact the performance of ACI Mercury Control Systems
- When SO_3 is removed upstream of ACI injection – the Mercury removal performance is improved by 40+%




Impact on Native Hg Capture with 6 ppm SO₃



Data Courtesy of Southern Company

Variable SO₃ and Sorbent Injection Test Data



Data Courtesy of Southern Company

Plant Daniel Schematic





Figure Courtesy of Southern Company

Variable SO₃ and Sorbent Injection Test Data



Data Courtesy of Southern Company



Plants With (or planning for) Hydrated Lime Injection Upstream of Their Air Heaters



Plant	Size
Asheville - 1	191 MW
Asheville - 2	185 MW
Roxboro - 1	369 MW
Roxboro - 2	671 MW
Roxboro - 3	685 MW
Roxboro - 4	700 MW
Mayo -1	736 MW
Crystal River - 4	739 MW
Crystal River - 5	739 MW
Ghent - 1	550 MW
Trimble County - 1	550 MW
Trimble County - 2	750 MW

Plant	Size
Belews Creek -1	1080 MW
Belews Creek - 2	1080 MW
Orlando Util Comm. - 1	465 MW
Orlando Util Comm. - 2	465 MW
Wateree - 1	370 MW
Wateree - 2	370 MW
Hammond - 4	578 MW
Bowen - 1	800 MW
Bowen - 2	789 MW
Bowen - 3	952 MW
Bowen - 4	952 MW
Wansley - 1	952 MW
Wanslet - 2	952 MW



Boilers Injecting Upstream of Air Heater

- Rationale for injecting upstream of air heater vs. downstream
 - ✓ Increased residence time
 - ✓ Increased time between air heater washes
 - ✓ Mercury removal
- All systems are targeted on SO_3 removal, not HCl or SO_2
- Some have run for over 2 years, and some are in design/planning stage





Experiences with Upstream Injection

- Have seen slower increase in ΔP resulting in longer times between air heater cleaning – from every 6 – 8 weeks to several months.
- Some report they clean air heaters anytime they can when the boiler is down so there is not good records of savings
- **Buildup of hydrated lime on air heater surfaces has not been a problem**



