

REINHOLD ENVIRONMENTAL Ltd.



2011 NO_x-Combustion Round Table & Expo Presentation

February 7-8, 2011, in Birmingham, AL / Hosted by Southern Company


All presentations posted on this website are copyrighted by Reinhold Environmental, Ltd (RE). Any unauthorized downloading, attempts to modify or to incorporate into other presentations, link to other websites, or obtain copies for any other uses than the training of attendees to RE's Conferences is expressly prohibited, unless approved in writing by RE or the original presenter. RE does not assume any liability for the accuracy or contents of any materials contained in this library which were presented and/or created by persons who were not employees of RE.

SCR Inspection : The Good and the Bad

Ronald L Richard
Senior Consultant
RE Consulting

A SCR inspection is not just looking at the catalyst

A thorough inspection will start at the boiler economizer and proceed through the outlet of the SCR box.



Economizer Bypass

- Look for cracks or deformation caused by thermal stress
- Look for ash deposits or ash erosion
- Check the condition of the dampers

LPA Screens

- Inspect the structural elements
- Inspect the screens for holes and thin areas



Source: Steag

SCR Inlet Ducts

- Ash deposits can give an indication of flow deviations across the duct. A larger ash deposit is a sign of a lower gas flow.
- Erosion of duct wall is a sign of very high gas flow



Turning Vanes

- Check that the vanes are clean and free from erosion damage
- Check that each vane is securely fastened to the support structure



Delta Wings

- Check that the wings are clean and free from erosion damage
- Check that each wing is securely fastened to the support structure



Static Mixers

- Check that the mixing vanes are clean and free from erosion damage
- Check that each mixing vane is securely fastened to the support structure



Ammonia Injection Grid

- Make sure all the components of the AIG are in place
- Make sure each injection hole is not plugged with ash or ammonium bisulfite deposits



Dampers

- With year round operation, dampers aren't being used as often
- If possible, one may want to stroke the dampers while someone is in the duct watching them travel to identify any spots where the dampers may tend to bind or rub
- Look for erosion or corrosion on the dampers and their frames

Rake Sootblowers


- Check the rake supports
- Check that the guide rollers are free to turn
- Look for erosion damage on the exterior of the rake arms
- Make sure the holes in all the nozzles are open



Sonic Horns

Check the inside of the horn bell for:

- Ash buildup in the cool wet area
- Corrosion and holes in the cool wet area



Catalyst

- It is not unusual to find a lot of ash and debris on top of the catalyst.
- Pay attention to the pattern across the SCR box.




Catalyst (cont.)

- After vacuuming the ash off the top of the catalyst, one needs to inspect and count the plugged cells in a representative number of catalyst modules



Catalyst (cont.)

- It is more difficult to count the percentage of cells plugged in a plate catalyst



Unburned Carbon

- One needs to minimize the amount of unburned carbon that accumulates on the catalyst.
- Large accumulations can lead to smoldering deposits or catalyst fires.

Charred Deposit in Catalyst



Catalyst (cont.)

- Check for catalyst erosion
- With plate catalyst the wire mesh will still be there but the catalyst will be missing
- With honeycomb catalyst the surface may look like an aerial view of a mountain range
- With plugged honeycomb catalyst the erosion may be hidden, look at the bottom side of the catalyst



Catalyst (cont.)

- Look for gas leakage between the catalyst modules indicating a bad seal
- Look for missing seal strips around the honeycomb catalyst elements



Sampling Plate Catalyst




Source: Argillon

Honeycomb Test Element



Sampling Grid

- Check that the sample lines are firmly attached and terminate in the correct location
- Look for holes in the lines
- The sample lines tend to plug or corrode holes through the tube wall at the hot/cold interface



Questions?